Submi

Submit 3 Copies to Approriate District	State of New	Mexico			
Office	Energy, Minerals and	Natural Resouces			
<u>DISTRICT I</u>	27			FORM C-103	
1625 N. French Dr., Hobbs, NM 88240			R	levised March 25, 1999	
<u>DISTRICT II</u>	OIL CONSERVATI	ON DIVISION	WELL API NO.	<u> </u>	
811 South First, Artesia, NM 88210	1220 South St. Fr	1220 South St. Francis Drive		36055	
DISTRICT III	Santa Fe, NM 87505		30-025- 36055 5. Indicate Type of Lease	-1003	
1000 Rio Brazos Rd., Aztec, NM 87410	= = - -, - · · - ··		STATE	 FEE	
<u>DISTRICT IV</u>			6. State Oil & Gas Lease No.		
1220 South St. Francis Dr., Santa Fe, NM 8750	15				
SUNDRY NOTICES AND REPORTS ON WELLS					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name		
PROPOSALS.)			THOMA	S LONG	
1. Type of Well:		· · · · · · · · · · · · · · · · · · ·	1		
☑ OIL WELL	GAS WELL OTHER				
2. Name of Operator			8. Well No.	· · · · · · · · · · · · · · · · · · ·	
Apache Corporation			6		
3. Address of Operator	9. Pool name or Wildcat				
6120 South Yale, Suite 1500 Tulsa, OK 74136			TUBB OIL AND GAS (60240)		
4. Well Location Unit Letter N	: 900 Feet From The SOUTH	Line and 2091	Feet From The WEST	Line	
Section 11	Township 22S Range	37E NMPM	County	LEA	
	10. Elevation (Show whether DF, RI	KB, RT, GR, etc.)			
	GR 33	48			
11.	Check Appropriate B	ox to Indicate Nature of Notice,	Report, or Other Data		
NOTICE OF	INTENTION TO:	SEQUENT REPORT OF:			
Perform Remedial Work	Plug and Abandon	Remedial Work		Altering Casing	

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/27/02-1/7/03

☐ Other

DRILLED 7-7/8" HOLE FROM 1446' TO 6260'.

Change Plans

1/8/2003

☐ Temporarily Abandon

Pull or Alter Casing

PROBLEMS WITH LOGGING TRUCK. ABORT LOGS-RD LOGGERS.

RIH W/143 JTS. (6269.63') 5-1/2", 17#, J55, LT&C CSG W/22 CENTRALIZERS. CMT SHOE @ 6260', FC @ 6213' W/950 SX 50:50 POZ C W/10% GEL + 5% SALT + 0.003 GPS FP-6L & 0.125 # /SX = 413 BBLS., 11.8 PPG SLURRY W/2.44 YIELD & 400 SX 50:50 POZ C W/2% GEL + 5% SALT + 0.003 GPS FP-6L = 92 BBLS, 14.2 PPGSLURRY W/1.29 YIELD. PLUG BUMPED & HELD. CIRC 361 SX CMT TO PIT.

✓ Other

Commence Drilling Operations

Casing Test and Cement Job

CMT. PROD. CASING

ND BOP. SET SLIPS, CUT OFF CSG.

RELEASE RIG @ 5:00 PM 1/7/03

OCD

Plug and Abandonment

CONDITIONS OF APPROVAL, IF ANY:			IVE HASTALE MARKETER		4 (9)3
APPROVED BY	THILE WAS A STATE OF THE STATE		- DATE JAN 1 4 5003		
(This space for State Use)					
TYPE OR PRINT NAME LARRY E. RADER				TELEPHONE NO.	(918) 491-4900
SIGNATURE Lary tobel		TTILE	TECH. COORDINATOR	- DRLG. DATE	1/8/2003
I hereby cerufy that the information above is true and complete the	best of my knowledge and belief.				