Submit 3 Copies to Approriate District

Office

DISTRICT

State of New Mexico Energy, Minerals and Natural Resouces

	FOR	M	C-103
Revised	March	25	1999

1625 N. French Dr., Hobbs, NM 88240			Revised March 25, 1999	
DISTRICT II	OIL CONSERVATION	N DIVISION	WELL API NO.	
811 South First, Artesia, NM 88210			30-025-36055	
DISTRICT III			5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410	,		☐ STATE	
DISTRICT IV			6. State Oil & Gas Lease No.	
1220 South St. Francis Dr., Santa Fe, NM 87503	i			
SUNDRY	NOTICES AND REPORTS ON WEL	LS		
	PROPOSALS TO DRILL OR TO DEEPEN OR P APPLICATION FOR PERMIT" (FORM C-101) I		7. Lease Name or Unit Agreement Name	
PROPOSALS.)			THOMAS LONG	
1. Type of Well: OIL WELL	GAS WELL OTHER			
2. Name of Operator	·		8. Well No.	
Apache Corporation			6	
3. Address of Operator	Tulas OV 74126		9. Pool name or Wildcat TUBB OIL AND GAS (60240)	
6120 South Yale, Suite 1500 4. Well Location	D Tulsa, OK 74136		TOBB OIL AND GAS (00240)	
Unit Letter N	900 Feet From The SOUTH	Line and 2091	Feet From The WEST Line	
Section 11	1	7E NMPM	County LEA	
	10. Elevation (Show whether DF, RKB, R GR 3348	T, GR, etc.)		
11.	Check Appropriate Box t	o Indicate Nature of Notice,	Report, or Other Data	
NOTICE OF INTENTION TO:		SUB	SEQUENT REPORT OF:	
Perform Remedial Work	Plug and Abandon	Remedial Work	☐ Altering Casing	
☐ Temporarily Abandon	Change Plans	Commence Drill	ing Operations Plug and Abandonment	
Pull or Alter Casing		Casing Test and	Cement Job	
Other		☑ Other	Spud & Cmt surface csg	
10 D				

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/26/2002 MIRU CAPSTAR RIG #8. SPUD 12-1/4" HOLE AT 0930. DRILL TO 1408' TMD.

12/27/2002

CONT. DRILLING 12-1/4" HOLE TO 1446'. CIRC. FOR CSG. SET 8-5/8" 24#, J-55, ST&C @ 1446. CEMEN' WITH 600 SACKS 65/35 CLASS "C" CEMENT/POZ W/6% BENTONITE GEL + 2% CALCIUM CHLORIDE + 0.125 #/SX CELLO FLAKE + 0.003 GAL/SK FP-6L MIXED AT 12.7 PPG, 1.88 CF/SX YIELD(201 BBL) & 250 SACKS CLASS "C" CEMENT + 2% CALCIUM CHLORIDE + 0.003 GAL/SX FP-6L MIXED AT 14.8 PPG. 1.35 CF/SX YIELD (60 BBL).

WOC. TEST BLIND RAMS & CASING TO 1000 PSI.

Thereby certify that the information and is true and considerations.	Diete of the bas of my knowledge and belief. THILE	TECH. COORDINATOR - DE	RLG. date	1/3/2003
TYPE OR PRINT NAME LARRY E. RA	DER	TI	ELEPHONE NO.	(918) 491-4900
(This space for State Use) APPROVED BY	CARCINIC SIGNED BY		DATE: LAM	(, ଓ ଅଧ୍ୟ
CONDITIONS OF APPROVAL, IF ANY:	OC RELD REPRESENTAT	IVE II/STAFF MANAGER	JAK	