

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-01917

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanagan D

9. WELL NO.

3 Unit Letter I

10. FIELD AND POOL, OR WILDCAT

Double X Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T-24-S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Bill J. Graham

3. ADDRESS OF OPERATOR

Box 5321, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980 FSL & 660 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3622 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Abandonment:

1-23-74 - spotted 25 sx plug @4915', filled hole w/10# brine w/salt gel. spotted 35 sx plug @ 3390', pulled tubing.

1-24-74 - tagged plug @ 2781', shot 4 1/2 casing at 2768', pulled casing, ran tubing to 1410', spotted 35 sx plug, spotted 35 sx plug @ 380', put 10 sx in surface and marker.

Location has been cleaned up and caliche pad ripped.

Casing left in hole - 4 1/2" from 4968' to 2768'
8 5/8" - 380' to surface

Old perfs - notch - 4979'

18. I hereby certify that the foregoing is true and correct

SIGNED

Beef Graham

TITLE

Owner

DATE 9-18-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

OCT 18 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

API 30-025-08142