



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. LC 068269-A
Unit P

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Frac</u>	<u>A</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 23, 1963

US Smelting - USA
Well No. 5 is located 990 ft. from N line and 330 ft. from E line of sec. 22

SE/4 SE/4 Sec. 22 24-S 32-S R6PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Double X Delaware Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3591 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Tagged bottom at 4930' and loaded hole w/oil.
2. Sand oil fraced w/5000 gals ref. crude w/1/40"/gal Adomite and 7500# 16-20 Mesh sand. Max. treating press. 4800 psi.
3. Tagged bottom at 4929'.
4. Put on pump. After recovery of lead oil well pumped 30 BO and 100 BW/24 hrs. on 14-5/8" SPM, 1 1/2" Pump.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tenneco Corporation by its Managing Agent Tenneco Oil Company

Address Box 307

Hobbs, New Mexico

By A. W. Lang A. W. Lang

Title Dist. Production Superintendent