SW/4 NW/4 Sec.23

(1/4 Sec. and Sec. No.)

(Field)

Double "X" Delaware

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	udget Bureau No. 42-R358.4 pproval expires 12-31-60.	
Lease Ng.	LC-062269	
Unit	Ε	

SUNDRY NOTICES AND REPORTS ON WELLS'

Ernest Federal			-
		April 23,	, 19 6 3
(INDICATE ABOVE BY CHECK	MARK NAT	RE OF REPORT, NOTICE, OR OTHER DATA)	
OTICE OF INTENTION TO ABANDON WELL			-
OTICE OF INTENTION TO PULL OR ALTER CASING	x	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT.	1
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	i i	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.	
OTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING.	
OTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
OTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	

The elevation of the derrick floor above sea level is 3609.46ft.

245

(Twp.)

DETAILS OF WORK

32E

(Range)

Lea County

(County or Subdivision)

NMPM

(Meridian)

New Mexico

(State or Territory)

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD - 5020'. 318' 8-5/8 surface casing. Notched @ 4923' & 4925'. Propose to plug as follows after mudding hole: 100' (4919'-5019'), 100' (50' in and 50' out of top of cut-off section of 4-1/2" casing, approx. 1950'-2050'), 100' (1300'-1400'), 100' (250'-350'), 10 sx plug in top of surface casing. Install & 4" marker 4' above ground with identification. Clean location and backfill pits.

in accordance with convenution between Mr. Standley and Mr. Bill Archer of Midland.

I understand that this plan of work must receive approval in writing	by the Geological Survey before operations may be commoned
Company Curtis Hankamer	
Address 1421 Bank of the Southwest Bldg.	
Houston 2, Texas	By Phil C. Flankamer
	Title Engineer