


Form 9-381a  
(Feb. 1961)

NOBBS



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **New Mexico**  
Lease No. **LC 062269 D**  
Unit **Wildcat**

SUNDRY NOTICES AND REPORTS ON WELLS

FEB 6 1961

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 6, 1961

**FEDERAL DELBASIN**  
Well No. 1 is located 660 ft. from [S] line and 660 ft. from [W] line of sec 35

SW 1/4  
(1/4 Sec and Sec No.)

T-24-S  
(Twp.)

R-32-E,  
(Range)

N. M. P. M.  
(Meridian)

Undesignated  
(Field)

Lea  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \* ft. Ground Level Elevation 3512'.  
\* Elevation will be reported when rig is moved in.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to drill and complete a well in the upper part of the Delaware Sand at an approximate total depth of 5000'.

8-5/8" OD 24 #/ft. J-55 new casing is to be set in a 12 1/4" hole at 375' with 325 sx. regular neat cement.

4 1/2" OD 9.50 #/ft. J-55 casing (new) is to be set in 6-3/4" hole, on bottom, at approximately 5000', and cemented with 100 sx. 50-50 Pozmix 2% gel, followed by 50 sx. of Latex cement; said cement volumes to be adjusted if necessary to cement up into the salt section.

The well will be drilled with rotary tools. Completion will be made by gun-perforating the pay sections and applying stimulation treatments based on information gained from preliminary natural tests.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SID W. RICHARDSON INC.**

Address **Box 1178,**

**MONAHANS, TEXAS**

By *Walter D. Owens*  
Assistant Division Manager

Title