## APPROVED JEEB 15 05

## HOBBS OFFICE COPY

GUINGT IN TRIPLICATED

United States
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

	_	-	
Land Offin	Hal	aha.	N.M.
Lenne Ma I			
· · · · · · · · · · · · · · · · · · ·	<b>3.4</b> 2	. 4.4.1	

DECEMPO

OEC 1 5 1958

MOTICE OF INTENTION TO CHANGE	PLAME	STOCKETON		n-err
NOTICE OF INTENTION TO TEST WAT	TER SHUT-OFF	-		OR ACIDIZING
THE OF MICHIGAN IS INCOME.	OR REPART WELL		*	
NOTICE OF INTENTION TO SHOOT OF MOTICE OF INTENTION TO PULL OR	A TED CASTA	SABORQUENT		
NOTICE OF INTENTION TO ABANDON	WELL		MAY WILL HEFFERY	
(Meica	ATE ABOVE BY CHECK M	MAK MATURE OF REPOR	T. HOTHE, OR STHUR BAT	×
			August 22.	
.M.N.T				•
all No is locat	ted 229.4.28 ft. fr	em. S line and	1 500.5 ft. from	line of sec. 1
E/4, SE/4, Section	15 265	32 E	N.M. P.M.	( - )
(Table 4	(Teles)	(Mange)	(Meddles)	-
Ildoat (Fide)	Los (Cour	sty or Bubdivision)	New_l	Maxico
e elevation of the derrick	foor shove see	level is 2185	fe .	
		AILS OF WOR		
	DET			
D Differ of and consists distribute.	المن معالمات وسافة والحالم	ALLS OF WOR	<b>^</b>	1
to names of and espected dapths to	chicative sands; show ing points, and a	alone, weighte, and long	pths of proposed engineer; recod works	indianto mudding John, es
agging program went	ing points, and a	alone, weighte, and long	pths of proposed engineer; recod works	indicate mudding jobs, on
Agging program went TD = 4652° - 4500° . 640° - 590	as follows:	in 6 3/4 inor	holes—	indianto modding Johe, es
Agging program went TD = 4652' - 4500' 640' - 590 25' plug in bottom	as follows: = 48 sacks = 16 sacks	in 6 3/4 inor	holes-	
Agging program went TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of	as follows: = 48 sacks = 16 sacks = of 10 3/4 surface pine	in 6 3/4 inor	h hole:-	<i>i (</i> 1 :
agging program went TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of hole and 4° out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
agging program went TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of hole and 4° out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
Agging program went  TD = 4652° - 4500°  640° - 590  25° plug in bottom 6° plug in top of hole and 4° out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
agging program went TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of hole and 4° out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
agging program went TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of hole and 4° out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
agging program went TD = 4652' - 4500' 640' - 590 25' plug in botton 6' plug in top of hole and 4' out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe	in 6 3/4 inor	hole:-	ipe 6° into th
Agging program went  TD = 4652' - 4500' 640' - 590 25' plug in bottom 6' plug in top of hole and 4' out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe th descripti	in 6 3/4 inormalist in 6 3	hole:-  De = 16 sacks  Placed 4½ p  p of 4½ pipe  H /  1.50	pipe 6° into th
agging program went  TD = 4652' - 4500' 640' - 590 25' plug in bottom 6' plug in top of hole and 4' out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe th descripti	in 6 3/4 inormalist in 6 3	hole:-  De = 16 sacks  Placed 4½ p  p of 4½ pipe  H /  1.50	pipe 6° into th
agging program went  TD = 4652° - 4500° 640° - 590 25° plug in bottom 6° plug in top of hole and 4° out wi  24-59 fsc. CR	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe th descripti	in 6 3/4 inormalist in 6 3	hole:-  De = 16 sacks  Placed 4½ p  p of 4½ pipe  H /  1.50	pipe 6° into th
Agging program went  TD = 4652' - 4500' 640' - 590 25' plug in bottom 6' plug in top of hole and 4' out wi	as follows: = 48 sacks = 16 sacks n of 10 3/4 surface pipe th descripti	in 6 3/4 inormalist in 6 3	hole:-  De = 16 sacks  Placed 4½ p  p of 4½ pipe  H /  1.50	pipe 6° into th

s. corrections received cryses 10-0400