

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Checklist Item No. 100-1
Revised August 31, 1985
1. LEASE DESIGNATION AND SERIAL NO.
LC-062749B
2. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection	7. UNIT AGREEMENT NAME #1
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Thompson Fed. #9
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, NM 88240	9. WELL NO. #2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit letter F 1980' FNL & FWL	10. FIELD AND POOL, OR WILDCAT Mason Delaware North
14. PERMIT NO. 30-025-08266	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19, T26S, R32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3195' D.F.	12. COUNTY OR PARISH Dea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) Install liner & Stimulate ☒	

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Notify OCD & BLM prior to R.U.

1. Clean out wellbore to TD
2. Plugback w/sand/Cal-Seal to 4295'
3. 61H w/liner assy, btm. of liner at 4052'
4. Cmt liner in hole w/50 lbs Class C cmt. After 15 hr are pumped, the hanger packing elements will be set to. Agree csg leaks @ 9176', 9197', & 9218'.
5. WOC 24 hrs., then DO cmt, Cal-seal & sand.
6. Stimulate w/1000 gals 15% HCL-NE-FE
7. RTH w/inj. equip.
8. Return to inj.

18. I hereby certify that the foregoing is true and correct

SIGNED W.W. Baker W.W. Baker TITLE Administrative Supr. DATE 1/24/90

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 2-5-90
CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side