L

(SUBMIT IN TRIPLICATE)

UNITED STATES Lease No. O DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Lease No.	06951	š
Unit	L	
	3 1	

1 SECTION TO DRILL	XXX
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS.	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO BE DOWN OF THE	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
	MADY
	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Wilder 25	June 1 , 19
Vell No. 3 is located 1980 ft. f	from S line and 660 ft. from W line of sec. 25
S 1/4 25 26 8	32 (***********************************
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
AT Mar Delaware	(Mendan)
(Field) (Cou	unty or Subdivision) (State or Territory)
location to an artistical	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) 1 a well with rotary tools at the above of 4040. Casing will be set in
will be complied with. The following casing paying the approximately 100	other special requirements
will be complied with. The following casing payith approximately 400 sacks set at 4640' with approximately 400.	attern is planned: 8 5/8" set at 700; cement to return to surface; 4 1/2" tely 170 sacks, cement to return to
The following casing payith approximately 400 sacks let at 4640' with approximately .000'. understand that this plan of work must receive approval approximately .000'.	attern is planned: 8 5/8" set at 700's, cement to return to surface; 4 1/2" tely 170 sacks, cement to return to
will be complied with. The following casing payith approximately 400 sacks set at 4640' with approximately 400.	attern is planned: 8 5/8" set at 700's, cement to return to surface; 4 1/2" tely 170 sacks, cement to return to
The following casing payith approximately 400 sacks let at 4640' with approximately .000'. understand that this plan of work must receive approval approximately .000'.	attern is planned: 8 5/8" set at 700's, cement to return to surface; 4 1/2" tely 170 sacks, cement to return to