 X	

	reperoval expires 12-31-60,
(SUBMIT IN TRIPLICATE)	Land Office Las Cruces
UNITED STATES	Lease No. 069515
RTMENT OF THE INTERIOR	Unit
	· ·

DEPAR GEOLOGICAL SURVEY

MOTION OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHIPT OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO BE DOLL OF DEDAID WELL	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO SHOOT OR ACIDITE	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ABANDON WELL	SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)
w. W. Wilder	June 26 19 5
Well No. 6 is located 1980 ft. from	
with he at a	7.7 **
(1/ See and Co. 3T.)	Range) (Meridian)
Li Var Deleware Las	New Kext co
(Field) (County or	Subdivision) (State or Territory)
he elevation of the derrick floor above sea lev	.1.1.
the deriver noon above sea lev	ci 18 It.
DETAII	S OF WORK
itate names of and expected depths to objective sands; show size	s, weights, and lengths of proposed casings; indicate mudding jobs, cement her important proposed work)
cordance with USOS standards :	vell at the above location with rot 5'. Casing will be cemented in and other special regulations will
cordance with USGS standards as complied with. The following casing patter of with approximately LOG and	1. Casing will be comented in
cordance with USGS standards as complied with. The following casing patter of with approximately 400 sacist at 4685' with approximately 000'.	or is planned: 7 5/8" OD set at
cordance with USGS standards as complied with. The following casing patter 00' with approximately 400 sacket at 4685' with approximately 100'. Tunderstand that this plan of work must receive approval in whompany Continental Oil Company ompany Box 65	or Casing will be cemented in and other special regulations will on in planned: 7 5/8" OD set at as, cement to circulate; 4 1/2" OD 170 sacks, cement to return to
cordance with USOS standards a complied with. The following casing patter of with approximately 400 sacks at 4685' with approximately 900'. Tunderstand that this plan of work must receive approval in with approximately continental Oil Company	or is planned: 7 5/8" Of set at as, cement to circulate; 4 1/2" of 170 sacks, cement to return to