



# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico OCC  
HOBBS OFFICE

WELL SERIALIZED 10:07  
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Continental Oil Company

W. W. Wilder

(Company or Operator)

(Lease)

Well No. 7, in NW 1/4 of SE 1/4, of Sec. 25, T. 26, R. 32, NMPM.

El Mar Delaware

Pool, Lea

County.

Well is 1980 feet from South line and 1980 feet from East line

of Section 25. If State Land the Oil and Gas Lease No. is

Drilling Commenced 7-12, 1959. Drilling was Completed 7-22, 1959.

Name of Drilling Contractor Dexter Drilling Co.

Address Wichita Falls, Texas

Elevation above sea level at Top of Tubing Head 3122' DF. The information given is to be kept confidential until 19.

## OIL SANDS OR ZONES

No. 1, from 4625' to 4649' No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7 5/8	24#	New	641	Guide			
4 1/2	9.5#	New	4749	Float		4625-32'	
						4636-49'	

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	7 5/8	650	325	Pump & Plug		
6 1/4"	4 1/2	4719	175	Pump & Plug		

## RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sandfraced with 2,000 gals. crude, 3,000# sand, 100# Adomite.

Result of Production Stimulation Flowed 58 BO, 13 BW, in 6 hrs., 20/64" choke, w/34.5 MCFGPD.

Depth Cleaned Out

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 4719 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Put to Producing.....**7-26**....., 19 **59**

OIL WELL: The production during the first 24 hours was.....284.....barrels of liquid of which.....82.....% was oil; .....% was emulsion; .....18.....% water; and.....% was sediment. A.P.I. Gravity.....40.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

### Southeastern New Mexico

T. Anhy.....600		T. Devonian.....		T. Ojo Alamo.....	
T. Salt.....750		T. Silurian.....		T. Kirtland-Fruitland.....	
B. Salt.....4359		T. Montoya.....		T. Farmington.....	
T. <del>XXXXX</del> Dela Lm 4581		T. Simpson.....		T. Pictured Cliffs.....	
T. <del>XXXXX</del> Dela Sd 4621		T. McKee.....		T. Menefee.....	
T. Queen.....		T. Ellenburger.....		T. Point Lookout.....	
T. Grayburg.....		T. Gr. Wash.....		T. Mancos.....	
T. San Andres.....		T. Granite.....		T. Dakota.....	
T. Glorieta.....		T. ....		T. Morrison.....	
T. Drinkard.....		T. ....		T. Penn.....	
T. Tubbs.....		T. ....		T. ....	
T. Abo.....		T. ....		T. ....	
T. Penn.....		T. ....		T. ....	
T. Miss.....		T. ....		T. ....	

From	To	Thickness in Feet	Formation
0	600	600	Redbeds
600	750	150	Anhydrite
750	4359	3609	Salt & Anhydrite
4359	4581	222	Anhydrite
4581	4621	40	Black Shale
4621	4719	98	Sand Stone

TD 4719', DF 11'. Oil trucked by Permian Oil Company.

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Continental Oil Company Address Box 68, Eunice, New Mexico  
Name J. R. Parker Position or Title District Superintendent