

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(COUNT INSTRUCTIONS ON REVERSE SIDE)Form approved
Budget Bureau No. 42-81114

5. LEASE DESIGNATION AND SERIAL NO.

LC-0 69515

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>Wildcat</i>
3. ADDRESS OF OPERATOR <i>Box 460, Hobbs, N.Mex. 58240</i>	9. WELL NO. <i>19</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>1980' FNL : 660' FNL of sec. 25, T-26S, R-32E, in Lea County, N.Mex.</i>	10. FIELD AND POOL, OR WILDCAT <i>Stuart Delaware Pool</i>
14. PERMIT NO.	11. SEC., T., E., M., OR B.L. AND SURVEY OR AREA <i>Sec. 25, T-26S, R-32E</i>
15. ELEVATIONS (Show whether DF, RT, Cr, etc.) <i>3129 DF</i>	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N.Mex.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It was determined that holes have developed in the casing. Cut casing into at 614'. Ran clean-up mill and dressed top of fish. Ran Bowen lead-seal casing bowl with 19 joints of 4 1/2" 9.5 # Casing. Pulled casing to 25,000 # tension and tested with 1,000 # for 30 minutes. Tested OK.

ILLEGIBLE

18. I hereby certify that the foregoing is true and correct

SIGNED *W. L. Gordon*TITLE *Adm. Section Chief*DATE *9-30-68*

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

U.S.S. 5 FILE

*See Instructions on Reverse Side

OCT 1 1968

J. L. GORDON
ACTING DISTRICT ENGINEER