

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date December 16, 1959 Title District Superintendent

The summary on this page is for the condition of the well at above date.

Commenced drilling 11-29-59 1959 Finished drilling 12-9-59 1959

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 4630 to 4644 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

	Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
7	5/8	353	175	Pump & plug		
4	1/2	4675	375	Pump & plug		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 4575 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

....., 19..... Put to producing ~~December 13~~ 1959 19.....

The production for the first 24 hours was 159 barrels of fluid of which 82% was oil; -----% emulsion; 18% water; and -----% sediment. Gravity, °Bé. 46-----

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. -----

EMPLOYEES

----- J. W. Peeters -----, Driller
----- J. O. Cole -----, Driller
----- D. G. Knott -----, Driller
-----, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	587		Surface caliche & Red Beds
587	865		Anhydrite
865	4358		Salt & Anhydrite
4358	4582		Anhydrite
4582	4626		Dela Lm.
4626	4675		Dela Sd.

TD 4675 Sd, DF 11', elev 3132' DF, pay Dela Sd 4630-44, net effective pay 14', csg Ft 4 1/2" at 4675, perf 4630-44 w/4 JOPF. IP Flwd 128 Bbls 40 deg grav oil, 6 BW in 22 hours, 14/64" chk, TP 275 lbs, OP 275 lbs, W/86.8 MCFGPD, GOR 622, DOR 139 Bbls. Est daily allow 36 HO. TRTD W/250 gals acid, 2000 gals crude, 3000 lbs sand, 100 lbs Adomite. PL Conn Permian Oil Company. Drilg started 11-28-59, comp 12-9-59, TSTD 12-13-59. Tops: Rustler 587, Salt 865, Base Salt 4358, Dela LM 4582, Dela Sd 4626. Rig released 12-9-59.

Tops picked from electric log

