

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
E-5898

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name BELL LAKE UNIT
2. Name of Operator Continental Oil Company	8. Farm or Lease Name BELL LAKE STATE 3
3. Address of Operator P. O. Box 460, Hobbs, New Mexico 88240	9. Well No. 5
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 24-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat BELL LAKE Penn (Atoka)
15. Elevation (Show whether DF, RT, GR, etc.) 3652' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

RIH w/Tbg to 13,330' & SPOT 75 SX CLASS "H" Cmt to $\pm 12,900'$
& Pull Tbg. Run Free Point & cut and Pull 7" OD CSG From
 $\pm 10,750'$. RIH w/Tbg & SPOT 70 SX CLASS "H" Cmt From 10,800 -
10,600' OVER TOP OF CUT OFF CSG & Pull Tbg. Run Free Point
ON 9 7/8" CSG. Run 4 Shots Above Free Point to Determine
IF 9 7/8" or 13 3/8" ANNULUS are Pressured up. Kill IF Necessary
with 9.5 PPG Brine. Cut & Pull 9 7/8" CSG From $\pm 6000'$. RIH w/Tbg
& SPOT 200 SX CLASS "C" Cmt From 6100-5900'. Pull Tbg & SPOT
100 SX CLASS "C" Cmt From 5250-5150' and 10 SX Surface Plug.
Erect Dry Hole Marker & Restore Surface.

* Addition - 100' plug inside 13 3/8" cgs. opposite top of
Salt @ $\pm 1460'$ - JWR-N.M.O.C.C.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Wm. R. Butterfield TITLE ADMIN. SUPERVISOR DATE 7-23-76

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NMOCC (5). Exxon, Lowe, Phillips, Bass. File

RECEIVED

JUL 28 1976

OL CONSTITUTIONAL CO. INC.
1000 N. B.