



AREA 640 ACRES  
LOCATE WELL CORRECTLY

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

F. R. JACKSON

(Company or Operator)

STATE

(Lease)

Well No. 1 in SW  $\frac{1}{4}$  of NW  $\frac{1}{4}$  of Sec. 21 22, T. 24 S., R. 33 E., NMPM.

Wildcat

Pool, Lea County.

Well is 1980 feet from North line and 660 feet from West line

of Section 21. If State Land the Oil and Gas Lease No. is Unknown - Sublease from Phillips

Drilling Commenced May 17, 1958 Drilling was Completed June 8, 1958

Name of Drilling Contractor Western Drilling Company

Address 902 Lubbock National Bank Building, Lubbock, Texas

Elevation above sea level at Top of Tubing Head 3594 The information given is to be kept confidential until Not Confidential, 19    

### OIL SANDS OR ZONES

No. 1, from None to      No. 4, from      to       
No. 2, from      to      No. 5, from      to       
No. 3, from      to      No. 6, from      to     

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to      feet.  
No. 2, from      to      feet.  
No. 3, from      to      feet.  
No. 4, from      to      feet.

### CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
<u>8 7/8</u>	<u>32</u>	<u>New</u>	<u>690</u>				<u>Surface Protection</u>

### MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>8 5/8</u>	<u>32</u>	<u>New</u>	<u>690</u>			<u>Surface Protection</u>
<u>12 7/8</u>	<u>8 7/8</u>	<u>640</u>	<u>500</u>			<u>Perforation</u>

### RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

None

Result of Production Stimulation

Depth Cleaned Out

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 5509 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Put to Producing PEA C-9, 1958

**Gravity**.....

Length of Time Shut in.....

## Northwestern New Mexico

T. Anhy.....	1220	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....		T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	4978	T. Montoya.....	T. Farmington.....
T. Yates.....		T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....		T. McKee.....	T. Menefee.....
T. Queen.....		T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....		T. Granite.....	T. Dakota.....
T. Glorieta.....		T. Delaware Ls 5230	T. Morrison.....
T. Drinkard.....		T. " Ss 5262	T. Penn.....
T. Tubbs.....		T. ....	T. ....
T. Abo.....		T. ....	T. ....
T. Penn.....		T. ....	T. ....
T. Miss.....		T. ....	T. ....

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Position or Title.....Consultant Geologist.....