

APPROVED

JBS OFFICE, C.

Form 9-281a
(Feb. 1961)

AUG 21 1961

Budget Bureau No. 42-R200.4.
Approval expires 12-31-66.

			X

E. W. STANDLEY
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Inspected 5-11-61
OK for abduct. JLL

Land Office **Las Cruces**

LC 062748

Unit _____ E

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Bradley 13

April 13 19 61

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 13

SE/4 Section 13
(1/2 Sec. and 1 Sec. No.)

26-S

(Twp.)

33-E
(Range)

NMPM
(Meridian)

Bradley Delaware
(Field)

Lea

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3368 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 5375', KB 13', ELEV 3368 KB, CSG PT 4½ @ 5375', PERF DELA SD, 5284-86 W/4 JSPP BY COLLAR LOG. LOG COMPARISON: 5284 ON GR/COLLAR LOG IS 5284 ON SONIC LOG & 5278 ON CORE. TRTD W/500 GAL MUD ACID FOL BY 2000 GAL FRAC USING 3000 LBS 20/40 SD & 1000 LBS 4/8 SD PLUS 100 LBS "ADOMITE". ON LAST 500 GAL OF FRAC, SCREENED OUT. REVERSED OUT SD. TOTAL SD IN FORM - 2500 LBS 20/40 & 500 LBS 4/8. AFTER TRMT FAILED TO REC LOAD. NO OIL OR GAS IN COMMERCIAL QUANTITIES OBTAINED. CUT OFF 4½ CSG AT 4500' & PULLED SAME. SET PLUGS 5375-5475 W/10 SX CMT, 4390-4500 W/25 SX, 1040-1150 W/25 SX, 265-375 W/25 SX & 15 SX AT SURF. INTERVALS BETWEEN PLUGS FILLED W/10 LB MUD. ERECTED 4" MARKER EXTENDING 4' ABOVE SURF W/WELL NAME & LOC INSCRIBED THEREON. LOC RESTORED TO ORIG COND. TOPS: T/HUSTLER - 800. T/SALT - 1145, B/SALT - 4988, T/LAMAR LM - 5232', T/DELA SD - 5276. DRIG STARTED 1-20-61 COMP 1-29-61. PLUGGING STARTED 4-10-61, COMP 4-12-61.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address P. O. Box 68, Eunice, New Mexico

By

Title District Superintendent