

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. LC 062748  
Unit 1

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<b>X</b>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 13  
SE 1/4 Section 13 26-5 33-E NM  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Bradley Delaware Lee New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3368 ft.


## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TO 5375', KB 13', ALLV 3368 KB, CNO PT 4 1/2" = 5375', PLUG DELA SD, 5284-86 1/4 JSTP BY COLLAR LOG. LOG COMPARISON: 5284 ON GR/COLLAR LOG IS 5284 ON SONIC LOG & 5278 ON CORN. TEND 1/500 GAL MUD ACID FOL BY 2000 GAL FRAC USING 3000 LBS 20/40 SD & 1000 LBS 4/8 SD PLUS 100 LBS "ADAMITE". ON LAST 500 GAL OF FRAC, SCREENED OUT. REVERSED OUT SD. TOTAL SD IN FURN - 2500 LBS 20/40 & 500 LBS 4/8. AFTER TEST FAILED TO RES LOAD. NO OIL OR GAS IN DAMAGERAL QUANTITIES OBTAINED. CUT OFF 4 1/2 CNG AT 4500' & FULLED SAME. SET PLUGS 5375-5475 1/10 SX GRT, 4390-4500 1/25 SX, 1040-1150 1/25 SX, 265-375 1/25 SX & 15 SX AT JSTP. INTERVALS BETWEEN PLUGS FILLED 1/10 LB MUD. ERRECTED 4" HURLES EXTENDING 4' ABOVE JSTP 1/4 SX NAME & LOG INSCRIBED THEREON. LOG RESTORED TO ORIG COND. TOPS: T/WISTLER - 800. T/SALT - 1145, B/SALT - 4988, T/LAHAN LM - 5232', T/DELA SD - 5276. DRIG STARTED 1-20-61 COMP 1-29-61. PLUGGING STARTED 4-10-61, CNG 4-15-61.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress P. O. Box 68, Eunice, New MexicoBy [Signature]Title District Superintendent



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. LC 062748  
Unit F

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Bradley 13 April 3, 1961

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 13

SE/4 Sec. 13 (1/4 Sec. and Sec. No.) 26-N (Twp.) 33-E (Range) NM (Meridian)

Bradley Delaware (Field) Lea (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3368 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Subject well was drilled to a TD of 5375'. No oil or gas in commercial quantities was encountered. It is now proposed to plug and abandon this well. Proposed plugging procedure consists of spotting 100' cement plug from TD to 5375', cutting off 4-1/2" casing w/inside cutters at 4500' and pulling same, spotting 25 sack cement plugs at 4500', 1150' (top of salt), 375' (bottom of surface casing) and a 10 sack plug at the surface, erecting a 4' x 4" steel marker and returning location to original condition. All intervals between plugs are to be filled with 10 lb. mud. A subsequent report will be filed upon completion of this work.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address P.O. Box 68

Manice, New Mexico

By J. R. Parker

Title District Superintendent

C/2 USGS NM000-2 (Direct) File