

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP DATE
(Other instruction
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. <i>NM 02791A</i>
2. NAME OF OPERATOR <i>Continental Oil CO.</i>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <i>Box 460 Hobbs, N. Mex.</i>	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>660' FSL + 1650' FWL, of Sec. 30, T-26S, R-33E, in Lea County, N. Mex.</i>	8. FARM OR LEASE NAME <i>Payne</i>
14. PERMIT NO.	9. WELL NO. <i>11</i>
15. ELEVATIONS (Show whether DF, FT, GN, etc.) <i>3102' DF</i>	10. FIELD AND POOL, OR WILDCAT <i>C. Mar. Delaware</i>
	11. SEC., T., R., N., OR BLK. AND SURVEY OR AREA <i>Sec. 30, T-26S, R-33E</i>
	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N. Mex.</i>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) *Convert to W.I.W.* ☒PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to convert this well to a water injection well by the following procedure:

Drill out cement & cast iron bridge plug from approx. 4730' to 4790'. Run cement lined tubing and packer and set packer at approx 4650'. Place well on injection

2. S. G. S. - 5 File
18. I hereby certify that the foregoing is true and correctSIGNED *M. E. Quattrone*TITLE *Adm. Section Chief*DATE *12-3-68*

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
DATE

DEC 4 1968

A. R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side