


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

8/3/49 411 Magnolia Bldg., Dallas, Texas
Date Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Bert Fields

Peggy E. Baetz

Well No. 1 in the _____

Company or Operator

Lease

C. of NE 1/4, S 1/4

of Sec. 13

T. 24S

R. 35-E

N. M. P. M.,

Wildcat

Field,

Lee

County.

The dates of this work were as follows:

7/28/49

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____

and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.) per M. Y. Soyester, U.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED S.D.I., 7/28/49.

1. Geological tops: Base of Red Beds - 1,652'; Top Brown Lime - 3,855';
Top of Yates - 3,902'.

2. Well Plugged & Abandoned 7/28/49, as follows w/Halliburton: 3,850' to 3,950' - 75 sacks; 1,550' to 1,650' - 75 sacks; 270' to 320' - 35 sacks; 14' to 24' - 5 sacks. 4" pipe marker 4' above ground cemented 6' below ground.

3. Each cement plug top was checked by lowering drill pipe to top of plug.

4. Above done per telephone conversation between M. H. Soyester and M. D.

Jackman, 7/28/49.

Witnessed by

L. E. Godard

Bert Fields

Tool Pusher

Name

Company

Title

Subscribed and sworn before me this 3rd

day of August

1949

I hereby swear or affirm that the information given above is true and correct.

Name

E. J. Stevens

Position

Agent

Representing

Bert Fields

Company or Operator

Charlene Milner

Notary Public

My commission expires

6/30/51

Address

411 Magnolia Bldg., Dallas, Texas

Remarks:

Name

Title