

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on the
reverse side)

Farm approved,
Budget Bureau No. 42 R1424.
LEASE DESIGNATION AND SERIAL NO.
NM-21644

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **Plug & Abandon**
2. NAME OF OPERATOR **Continental Oil Company**
3. ADDRESS OF OPERATOR **Box 460, Hobbs, NM 88240**
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface **990' FNL & 990' FEL Sec. 26**

7. UNIT AGREEMENT NAME **NMFW**
8. FARM OR LEASE NAME **LYNN B-1**
9. WELL NO. **2**
10. FIELD AND POOL, OR WILDCAT **Jalmat Yates 7 Rivers**
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA **Sec. 26, T-23S, R-36E**
12. COUNTY OR PARISH **Lea** 13. STATE **NM**

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3364' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☒
SHOOT OR ACIDIZE ☐ ABANDON* ☒
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) **Plug & Abandon**

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

IT IS Proposed To Plug and Abandon The Subject Well Due To Mechanical condition, See Attached Well History and Recommendation.
Plugging Procedures as Follows:
1. Run Tbg open ended and circulate & Load Hole w/10 LB. Brine
2. SPOT 25 SX class "c" CMT w/ 2% CA CL From 2928'-2689'
3. SPOT 25 SX class "c" CMT Plug From 1284'-1150'
4. SPOT 10 SX class "c" CMT From 96' to Surface
5. Erect Dry Hole Marker and Restore The Surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. G. Butler

TITLE

Admin. Supervisor

DATE

2-3-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

**APPROVED
AS AMENDED**

MAR 2 1977

BERNARD MOROZ

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS-5, NMFW-4, File