

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL <input checked="" type="checkbox"/>	

Hobbs, New Mexico

January 10, 1938

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Skelly Oil Co.

W. H. Combest

Well No. 1 in the

Company or Operator

Lease

NW NW SW

of Sec.

27

T.

23-

R.

36

N. M. P. M.,

Cooper

Field,

Lea

County.

The dates of this work were as follows: from Dec. 30, 1937 to Jan. 8, 1938 -

Notice of intention to do the work was (~~report~~) submitted on Form C-102 on Dec. 23 1938and approval of the proposed plan was (~~report~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Having drilled to total depth of 3950' well was acidized three times, showing no production. Well was then plugged back to 3560' with cement, lime and aquagel - plugged back to the bottom of the 7" casing which was set at 3565'. Casing was then perforated and well acidized in attempt to complete as gas well, but on test showed no gas or oil. Hole was loaded with mud-ladden fluid and 2934' 1" of 7" casing pulled - then 1402' 1" of 9-5/8" was pulled. Cement cap of 10 sacks was put on top of mud-ladden fluid, cellar filled and cemented 4" pipe in the cellar standing 4' above the surface of the ground.

Witnessed by John Pearce Olson Drilling Co. Foreman -

Name

Company

Title

Subscribed and sworn before me this 10

day of January, 1938

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name

Position District Superintendent

Representing Skelly Oil Co.

Company or Operator

My commission expires Dec. 10, 1940

Address Hobbs, New Mexico

Remarks:

Name

Title

DUPLICATE

Guy Shepard