

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

COPY TO

Field approval  
Approved by: *[Signature]*  
Special Agent in Charge, U.S. Bureau of Land Management  
U.S. Department of the Interior  
Washington, D.C. 20240

LC 030129 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back, or otherwise re-activate, an oil well or for proposals to plug back, proposals)

1. NAME OF OPERATOR *Plug & Abandon*  
*Continental Oil Company*  
2. ADDRESS OF OPERATOR  
*Box 460, Hobbs, N.M. 88240*  
3. LOCATION OF WELL (Show location clearly with reference to any state or township boundaries.)  
*660' FNL & 660' FEL of Sec. 28*

4. NAME OF OPERATOR

*NAFEX*

5. NAME OF FIELD NAME

*Lynn A*

6. WELL NO.

7. TYPE OF WELL (Oil, Gas, or Water)

*3 Rivers (SW) - Cooper Tail*

8. SURFACE, M., OR SURF. AND SURVEY OF AREA

*Sec 28 T-28S, R-36E*

9. COUNTY OR PARISH, STATE

*LER N.M.*

10. ELEVATION

11. ELEVATIONS (Show whether DE, RT, OR, etc.)

*3481' OF*

12. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. DESCRIBE PROPOSED OR COMPLETED OPERATIONS clearly show all pertinent details, and also pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.\*

*4-12-77 Circulated & cleaned out hole.*

*4-13-77 W/L w/Tbg & retainer. Set ret. at 2860'. Spot 50 Sx Class C cmt. w/2% CaCl<sub>2</sub> on top of retainer.*

*4-14-77 Tagged plug at 2605'. Perf 2 JSAP at 1400'-1402' W/L w/Tbg & retainer. Set at 1195'. Squeeze with 100 Sx. Thick set cmt. & 100 Sx Class C cmt. - 2% CaCl<sub>2</sub>. Left 15' cmt on top of retainer. Set 25 Sx plug from 400' to 265'. Pull Tbg. to 60'. Spot 100 Sx. plug 60' to surface.*

14. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

LLSGS (5), NAFEX (4), File