

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

WESTERN GAS COMPANY

Drawer "H", Bennett, New Mexico

Company or Operator **Combest** 1-X SE 1/4 NE 1/4 35 Address 23 So.
Well No. **Lynn** in of Sec. **Lea** T.
R. **36 E.** N. M. P. M. **1980** 660 Field. Section County.

Well is feet south of the North line and feet west of the East line of

If State land the oil and gas lease **F. No. P. Combest** Assignment No. **Jal, New Mexico**

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is **11-4-41** Address **1/5/42**Drilling commenced **E. C. Norwood Estate** Drilling was completed **Wichita Falls, Texas**Name of drilling contractor **3344** AddressElevation above sea level at top of casing **Not Confidential** feet

The information given is to be kept confidential until 19

	3500		05	IL SANDS OR ZONES	3568		76
No. 1, from	3520	to	25		No. 4, from		to
No. 2, from	3540	to	45		No. 5, from		to
No. 3, from		to			No. 6, from		to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from		to		feet.
No. 2, from		to		feet.
No. 3, from		to		feet.
No. 4, from		to		feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13	40	8	SO-Ch	301				
9-5/8	47	8	AOS	2795				
7	28	8	AOS	3488				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	13	301	250	Howco		
12 1/2	9-5/8	2795	500	"		
8-5/8	7"	3488	55	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3579 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 1-5-42 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Reed Driller J. Pryor Driller
CROSS Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 19

day of 19

Notary Public

My Commission expires

Bennett, New Mexico 1/5/42
Place Date

Name W. Davis

Position Production Sup't.

Representing WESTERN GAS COMPANY
Company or Operator

Address DRAWER H. BENNETT, NM.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
Surface	40	40	Caliche
40	1170	1130	Red beds, red sand
1170	1360	190	Anhydrite
1360	2760	1400	Salt, anhydrite.
2760	2950	190	Brown dolomite & Anhydrite
2950	3230	280	Brown-gray sandstone, brown dolomite.
3230	3500	270	gray-white dolomite & limestone.
3500	3578	78	gray limestone, and sandstone breaks.