

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B1413

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State LM "T"
3. Address of Operator Drawer D, Monument, New Mexico	9. Well No. 2
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>23S</u> RANGE <u>36E</u> NMPM.	10. Field and Pool, or Wildcat Jalmat Tansill Yates 7RQ
15. Elevation (Show whether DF, RT, GR, etc.) 3332'	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <u>Zone abandonment</u> <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-5-80 to 8-20-80 - Pulled (Getty's) rods, pump & tbq. Picked up work string of 2-3/8" tbq. & ran 4-3/4" bit to 3455'. Trip out & McCullough set CI bridge plug in 5 1/2" csg. at 3450' & dumped 10' of sand on top of bridge plug. Ran pkr. & set @ 3435' & tested bridge plug & tbq. to 2000#. Held OK. Re-set pkr. @ 2761', loaded csg. w/27 bbls. water & press. to 700#. Established inj. rate & Dowell squeezed Jalmat Tansill Yates Seven Rivers Queen zone thru 5 1/2" csg. perf. fr. 2930' to 3430' w/total of 1350 sks. class C cement w/additives in four stages. WOC and drld. out cement fr. 2765' to 3145' & tested squeeze job w/800# press. Held OK. Drld. cement to 3364' & cement stringers to 3395' & tested squeeze job w/800# press. Held OK. Circ. sand fr. top of bridge plug & drld. CI bridge plug at 3450'. Circ. hole clean to 3575'. Re-ran Getty's tbq., pump & rods. Jalmat Tansill Yates Seven Rivers Queen zone P&A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Adm. Ser. DATE 8/21/80

APPROVED BY Jerry Sexton TITLE Dist. L. Supv. DATE 8/25/80

CONDITIONS OF APPROVAL

411/Jalmat