

NEW MEXICO OIL CONSERVATION COMMISSION

HONORABLE OFFICE OF THE COMMISSION
FEB 14 1957
Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Jalmat Formation Yates-Seven Rivers County Lea
Initial _____ Annual X Special _____ Date of Test 12-7-56
Company Amerada Petroleum Corp. Lease State LMTM Well No. 2
Unit F Sec. 36 Twp. 23-S Rge. 36-E Purchaser Permian Basin Pipeline Co.
Casing 5-1/2" Wt. 15.5# I.D. 4.950" Set at 3455' Perf. 2930' To 3430'
Tubing 2-3/8" Wt. 4.7# I.D. 1.995" Set at 3512' Perf. 3506' To 3512'
Gas Pay: From 2930' To 3430' L 2930' xG 0.660 -GL 1934 Bar.Press. 13.2
Producing Thru: Casing X Tubing _____ Type Well G.O. Dual
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 12-10-48 Packer 3431' Reservoir Temp. 86°F

OBSERVED DATA

Tested Through (Pressure) (Gauge) (Meter) Type Taps Pipe

| No. | Flow Data | | | | | Tubing Data | | Casing Data | | Duration of Flow Hr. |
|-----|----------------------------|------------------------------|----------------|-------------------------|--------------|----------------|--------------|----------------|--------------|----------------------------|
| | (Prover) (Line) Size | (Choke) (Orifice) Size | Press. psig | Diff. h _w | Temp. °F. | Press. psig | Temp. °F. | Press. psig | Temp. °F. | |
| SI | | | | | | | | 841.8 | | 72-3/4 |
| 1. | 4" | 1.25" | 504.0 | 3.2 | 64 | | | 782.5 | | 23-1/4 |
| 2. | 4" | 1.25" | 506.8 | 6.8 | 67 | | | 723.2 | | 24 |
| 3. | 4" | 1.25" | 508.7 | 11.8 | 66 | | | 664.8 | | 24-1/2 |
| 4. | 4" | 1.25" | 503.2 | 19.2 | 69 | | | 604.7 | | 23-1/2 |
| 5. | | | | | | | | | | |

FLOW CALCULATIONS

| No. | Coefficient (24-Hour) | $\sqrt{h_w P_f}$ | Pressure psia | Flow Temp. Factor F _t | Gravity Factor F _g | Compress. Factor F _{pv} | Rate of Flow Q-MCFPD @ 15.025 psia |
|-----|--------------------------|------------------|------------------|--|-------------------------------------|--|--|
| 1. | 10.24 | 40.68 | 517.2 | 0.9962 | 0.9535 | 1.051 | 416 |
| 2. | 10.24 | 59.46 | 520.0 | 0.9933 | 0.9535 | 1.049 | 605 |
| 3. | 10.24 | 78.47 | 521.9 | 0.9943 | 0.9535 | 1.049 | 799 |
| 4. | 10.24 | 99.57 | 516.4 | 0.9915 | 0.9535 | 1.049 | 1011 |
| 5. | | | | | | | |

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c 1.793 (1-e^{-s}) 0.125

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 855.0 P_c 731.0

N₂ - 2.04%

| No. | P _w P _t (psia) | P _t ² | F _c Q | (F _c Q) ² | (F _c Q) ² (1-e ^{-s}) | P _w ² | P _c ² -P _w ² | Cal. P _w | P _w P _c |
|-----|---|-----------------------------|------------------|---------------------------------|---|-----------------------------|--|------------------------|----------------------------------|
| 1. | 795.7 | 633.1 | 0.7459 | 0.5564 | 0.0696 | 633.2 | 97.8 | 795.7 | .93 |
| 2. | 736.4 | 542.3 | 1.0850 | 1.1770 | 0.1471 | 542.4 | 188.6 | 736.5 | .86 |
| 3. | 678.0 | 459.7 | 1.4330 | 2.0530 | 0.2566 | 460.0 | 271.0 | 678.2 | .79 |
| 4. | 617.9 | 381.8 | 1.8130 | 3.2870 | 0.4109 | 382.2 | 348.8 | 618.2 | .72 |
| 5. | | | | | | | | | |

Absolute Potential: 1725 MCFPD; n .75COMPANY Amerada Petroleum CorporationADDRESS Drawer D - Monument, New MexicoAGENT and TITLE W.G. Abbott - District Engineer *W.G. Abbott*WITNESSED R.L. WestCOMPANY Permian Basin P.L. Co.

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressibility factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .