

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting 5½" Casing	X

February 18, 1949

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation State LMT Well No. 4 in the \_\_\_\_\_

Company or Operator

SE. NE 1/4 of Sec. 36, T. 23S, R. 36E, N. M. P. M.,  
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: February 17, 1949

Notice of intention to do the work was ~~(crossed out)~~ submitted on Form C-102 on February 17, 1949  
 and approval of the proposed plan was ~~(crossed out)~~ obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**3465' Total Depth Line.** Ran Schlumberger Electrical Survey & Their Gamma Ray & checked bottom @ 3465'. Ran 88 joints of 5½" OD, 15.5#, J-55, 8Rd. Thd. R-3, Spang Smls. Steel Casing (New) and set at 3465' and cemented with 450 sacks Trinity Reg. bulk cement & 50 sacks Incor quick set cement, plug stopped @ 3402' @ 5:15 A.M. 2-18-49 with final pump pressure 1300#. Ran 8 Model G Baker Centralizers, set @ 3230'-3260'-3290-3320-3350-3380-3410-3440, Spot welded first 6 collars.

Witnessed by <u>D.W. Gordon</u>	<u>Amerada Petroleum Corporation</u>	<u>Farm Boss</u>
Name	Company	Title

Subscribed and sworn before me this \_\_\_\_\_  
18th day of February 1949

Will Hails Taylor  
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Don Tipp  
 Position Asst. Dist. Supt.  
 Representing Amerada Petroleum Corporation  
 Company or Operator

My commission expires February 24, 1954 Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date FEB 24 1949

Reg. York  
 Name  
 Title