

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
APR 18 1949
OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

April 16, 1949
DateMonument, New Mexico
Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation State LMT Well No. 5 in the
Company or Operator Lease
NE $\frac{1}{4}$ NE $\frac{1}{4}$ of Sec. 36, T. 23S, R. 36E, N. M. P. M.,
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: April 16, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 15, 19 49
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3485' Total Depth, Lime. Ran Schlumberger E.S. & Gamma Ray Survey. Rigged up and Ran 110 joints 5 $\frac{1}{2}$ " OD, 8Rd. Thd. 15.5#, J-55 R-2 & R-3, Pittsburg S.S. Casing (New) and 2 joints 5 $\frac{1}{2}$ " O.D. 15.5# 8Rd. Thd. J-55, R-2, Spang Casing (New) and set at 3485' With 8 Baker Centralizers at 3260-3290-3320-3350-3380-3410-3440-3470' Spot welded first 6 collars on casing. Cemented with 450 sacks Trinity Regular bulk cement & 50 sacks Incor quick set cement. Plug stopped at 3418' at 5:00 A.M. 4-16-49 with final pump pressure 1300#.

Witnessed by D.W. Gordon Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

16th day of April 19 49Name Don TaylorPosition Asst. Dist. Supt.Representing Amerada Petroleum Corporation
Company or Operator

Notary Public

My commission expires COMMISSION EXPIRES MARCH 29, 1952 Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date APR 18 1949

Ray J. H. H. H.
Name
Oil & Gas Inspector
Title