


DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

July 11, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation State LMT Well No. 7A in the \_\_\_\_\_

Company or Operator \_\_\_\_\_ Lease \_\_\_\_\_  
NW 1/4 NW 1/4 of Sec. 36, T. 23S, R. 36E, N. M. P. M.,  
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: July 10, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on July 10, 1949 19\_\_\_\_  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3500' Total Depth, Lime. Rigged up and Ran 24 jts. 5 1/2" OD, 14#, Gr. C, 10VT, R-2, SS. Ssg. (SH) 710.14' & 87 jts. 5 1/2" OD, J-55, R-2, 8RT, SS. Csg. (New) 2795.94' Total of 111 jts. for 3508'. Csg. Set at 3500' with 8-5 1/2" Baker Centralizers at 3480'-3450'-3420'-3390'-3360'-3328'-3303' 3275'. Cemented casing with 450 sacks Lone Star Reg. & 50 sacks Incor Cement. Plug pumped to 3440' @ 6:45 P.M. 7-10-49 with Max. pressure of 600#. Ran Temperature Survey and found top of cement at 1290' Actual Fill 2210', Calculated fill 4140'. Ratio of Actual to Calculated fill 58.4%.

Witnessed by D.F. Surse Amerada Petroleum Corporation Foreman  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

11th day of July 1949

Will Hails, Notary Public

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name \_\_\_\_\_

Position Asst. Dist. Supt.,

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires MY COMMISSION EXPIRES MARCH 29, 1952

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date JUL 12 1949

Roy Yarbrough  
Name  
OIL & GAS INSPECTOR  
Title

# THE HISTORY OF THE UNITED STATES

OF THE

CONSTITUTION OF THE UNITED STATES

OF THE

CONSTITUTION OF THE UNITED STATES

OF THE

CONSTITUTION OF THE UNITED STATES

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE

OF THE