


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

August 9, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation

State IMF

Well No. 8 in the

Company or Operator

Lease

NW 1/4 NW 1/4

of Sec. 36

T. 23-S

R. 36-E

N. M. P. M.,

Langlie-Mattix

Field,

Lea

County.

The dates of this work were as follows: August 9, 1949

Notice of intention to do the work was ~~(crossed out)~~ submitted on Form C-102 on August 6, 1949 and approval of the proposed plan was ~~(crossed out)~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3480' - Total Depth - Lime. Connected 5 1/2" O.D. Casing, ran 10 Jts. 2-7/8" Drill Pipe and 100 Jts. 2-3/8" O.D., EUE, 4.7# S. S. Tubing and tested 5 1/2" Casing with 1000# for 1/2 Hour - Satisfactory. Temperature survey showed top of cement outside of 5 1/2" casing at 2055', actual fill 1425', ratio of actual to calculated fill 34.4%. Started drilling cement at 3412' at 6:45 A.M., 8-9-49, and drilled cement to 3480'. Tested 5 1/2" O.D. casing with 1000# for 1/2 Hour - satisfactory. Started drilling 4-3/4" hole at 3:08 P.M., 8-9-49.

Witnessed by D. W. Gordon Name Amerada Petroleum Corporation Company Farm Boss Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

9th day of August 19 49

Name D. F. Furse

Willie Hain, Jr., Esq.

Notary Public

Position Foreman

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires March 29, 1952

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

AUG 15 1949

Notary Public  
Name J. L. QUAS  
Title INSPECTOR