


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | Report On Setting Casing | X |

July 27, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation State INT Well No. 8 in the _____

Company or Operator

Lease

NW 1/4 NW 1/4 of Sec. 36, T. 23S, R. 36E, N. M. P. M.,

Langlie-Mattix Field, Lea County.

The dates of this work were as follows: July 26, 1949

Notice of intention to do the work was ~~approved~~ submitted on Form C-102 on July 26, 1949

and approval of the proposed plan was ~~approved~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

1224' - Total Depth - Anhydrite. Rigged up and ran 2 Jts., 86.10' of 8-5/8" O.D. 28#, Grade H-40, Range 3, 8-Rd. Thd., S. S. New Casing and 28 Jts., 1120.67', of 8-5/8" O.D., 32#, Grade J-55, Range 3, 8-Rd. Thd., S. S. New Casing and set at 1219' and cemented with 575 sacks of Lone Star Bulk cement and 50 sacks of Incor cement. Plug pumped to 1119' at 2:30 PM, 7-26-49. Maximum pump pressure 1200#.

Witnessed by Don W. Gordon Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

27th day of July 1949

Name Don W. Gordon

Will Hails Taylor
Notary Public

Position Asst. District Superintendent

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

AUG 2 1949
Date

H. M. Sweeney
Name
Engineer
Title