## NEW MEXICO OIL CONSERVATION COMMISSION

## SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the

advisable, or the rejection by the Commission or ag and work should not begin until approval is obta the Commission.	ained. Se	e additional instructi	ons in the Rules and Regu	ations of
Indicate natur	re of not	ice by checking below	r:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	x		NTION TO SHOOT OR TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS			NTION TO PULL OR ALTER CASING	
OTICE OF INTENTION TO REPAIR WELL	_	NOTICE OF INTE	NTION TO PLUG WELL	-
OTICE OF INTENTION TO DEEPEN WELL				
	Eo	bbs, New Moriec	June 20, 1949 Date	
IL CONSERVATION COMMISSION, anta Fe, New Mexico.  Tentlemen:  Collowing is a notice of intention to do certain we				
Cities Service Oil Company St Company or Operator L	ease		Well No. 1 in	C SW NW
f Sec. 2 T. 245 R. 36	N N	. М. Р. М	Langlie-Mattix	Field
FOLLOW INSTRUCTIONS IN THE R Total depth 1266 anhydrite.	Pann. 3	8 jts. or 1849.	70' of 8-5/8" OD 24/	8 Rt.
	Run 3 sements set 3	8 jts. or 1869. d with 600 sack	70° of 8-5/8" OD 24/ 2. Plug down at 5:0	0 PM.,
Total depth 1266' anhydrite. J-55 SS casing, set at 1262.50' & 6 6/20/49. Cement will be allowed to	Run 3 sements set 3	8 jts. or 1869. d with 600 sack	70° of 8-5/8" OD 24/ 2. Plug down at 5:0	0 PM.,
Total depth 1266' anhydrite. J-55 SS casing, set at 1262.50' & 6 6/20/49. Cement will be allowed to	Run 3 sements set 3	8 jts. or 1869. d with 600 sack	70° of 8-5/8" OD 24/ 2. Plug down at 5:0	0 PM.,
Total depth 1266' anhydrite. J-55 SS casing, set at 1262.50' & 6 6/20/49. Cement will be allowed to	Run 3 sements set 3	8 jts. or 1869. d with 600 sack	70° of 8-5/8" OD 24/ 2. Plug down at 5:0	0 PM.,
Jun 2 4 1949	Ran 3	8 jts. or 1849. d with 600 sack i6 hours before	70° of 8-5/8" OD 24/ 2. Plug down at 5:0	O PM.,
Jun 2 4 1949	Ran 3	8 jts. or 1949. d with 600 sash 6 hours before	70° of 8-5/8° OD 24/ 2. Plug down at 5:0 testing for shut off	O PM.,
Jun 2 4 1949	Ran 3	By	70' of 8-5/8" OD 24/2. Plug down at 5:0 testing for shut off	O PM.,
J-55 SS casing, set at 1248.30° & 6/20/49. Coment will be allowed to Corner Cuculated	Ran 3	By  Position  Send com	70' of 8-5/8" OD 24/2. Plug down at 5:0 testing for shut off testing for shut of testing for shut o	o PM.,