

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New MexicoMarch 23, 1950

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Cities Service Oil Co. State "Y" Well No. 1 in SW NW SW  
Company or Operator Lease  
of Sec. 2, T. 24S, R. 36E, N. M. P. M., Langlie-Mattix Field.  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Total depth 3731' lime. It is proposed to plug and abandon this well. Drill Stem Test #1 was run with packer set at 2960', tested 79' with no show of oil or gas. Drill Stem Test #2 was made from 3138' to 3225' (tested 87') small show of gas and no oil. Drill Stem Test #3 was made from 3548' to 3589' (41') tested with no show of oil. Drill Stem Test #4 was run from 3591' to 3639' (48' tested) with no show of oil or gas. Drill Stem Test #5 was run with packer set at 3709' (tested 22') with slight show of gas, no oil and recovered 120' of sulphur water. Since there were no show of oil and small shows of gas, it was decided to plug and abandon as follows: Spot 25 sacks of cement at 3700', 25 sacks at 1200'; and cement at surface with 25 sacks. P & A cite is to be marked as required.

Approved 1950 3 23 1950, 19\_\_\_\_  
except as follows:

Cities Service Oil Company  
Company or Operator

By [Signature]

Position Dist. Supt.  
Send communications regarding well to

Name R. W. ElyAddress Drawer GHobbs, New Mexico

OIL CONSERVATION COMMISSION

By [Signature]Title INSPECTOR

1/6/11  
1/6/11