

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions
reverse side)

Form approved:
Budget Bureau No. 1004-0113
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. <u>LC-030467-B</u>	
2. NAME OF OPERATOR Tenison Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 8140 Walnut Hill Lane, Suite 601, Dallas, TX. 75231		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' from N line & 660' F W line Sec. 3 T24S R36E <i>Unit E</i>		8. FARM OR LEASE NAME Vaughn "B" 3	
14. PERMIT NO.		9. WELL NO. 3	
15. ELEVATIONS (Show whether OF, RT, GR, etc.) GR 3389		10. SECTION, T., R., M., OR BLM. AND SURVEY OR AREA S3 T24S R36E	
		11. COUNTY OR PARISH Lea	
		12. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Proposed Well Work

1. Pull rods, pump & tbg.
2. Set retrievable bridge plug at 3420'.
3. Perforate 5½" csg. @ following points w/2 shots at each perforating point;
3416', 3388', 3381', 3360', 3335', 3333', 3298', 3296', 3295', 3254', 3251',
3247',
4. Acidize with 1500 gal. of 15% inhibited acid.
5. Pull retrievable bridgeplug.
6. Run tbg., rods & pump.
7. Put well on production.

RECEIVED
JUN 27 11 28 AM '91
CARLSON
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Operations Manager

DATE

June 21, 1991

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

7-5-91

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

JUL 09 1991

002
MCBBS OFFICE