## NEW MEXICO STATE LAND OFFICE

## OFFICE OF THE STATE GEOLOGIA!

SANTA FE, NEW MEXICO

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas inspector if possible.

nspector if possible. Indicate nature	of rep	ort by checkin	<b>6</b> · ·	•		
REPORT ON BEGINNING DRIRLLING OPERATIONS  REPORT ON RESULT OF SHOOTING WELL  REPORT ON RESULT OF TEST OF WATER SHUT-OFF		REPORT ON DEEPENING WELL  REPORT ON PULLING OR OTHERWISE ALTERING CASING  REPORT ON REPAIRING WELL				
REPORT ON RESULT OF ABANDONMENT						
OF WELL Wink, Texas		September 24	. 1935			'
·		Place		D	ate	
Mr R. H. Wells State Geo Santa Fe, N. Mex.				,, ,	3.° <i>i</i>	
Following is a report on the work done at the Skelly 011 Company B	and the	results obtaine	d under	the head	ding note	d above at in the
Company of Operator Lease	•	A 4 44				
que /a que /a of Sec 3	<b>,</b>		, R	7003	N.	M. P. M.
Goorar Oil Field,		Les	1075			County.
The dates of this work were as follow Notice of intention to do the work was	7S:	September 2	1, 1935		.03	or
Drilled cement plug and bailed hole	to bot	and both te	and the	n let s	itand fo	r 12 hou. e effect
	to bot	tom, 3146°, and both te	and the	n let s	itand fo	r 12 hou e effect
Drilled cement plug and bailed hole	to bot	tom, 3146°, and both te	and the	n let s	itand fo	r 12 hou e effect
Drilled cement plug and bailed hole	to bot casing good	I hereby sigiven above is	and the sts sho	affirm the	etand for to b	9 911000
Drilled cement plug and bailed hole Then applied 600# water pressure to ively shut off and pipe cemented in  Subscribed and sworn to before me	to bot casing good	tom, 3146', and both te shape.	and the sts sho	on let sowed wat	etand for to b	9 91100
Drilled cement plug and bailed hole Then applied 600# water pressure to ively shut off and pipe cemented in  Subscribed and sworn to before me	to bot casing good	I hereby sigiven above in Name	wear or s true a	affirm the	hat the i	nformation
Drilled cement plug and bailed hole Then applied 600# water pressure to ively shut off and pipe cemented in  Subscribed and sworn to before me	to bot casing good	I hereby sigiven above in Position	wear or s true and SKELL	affirm the correct of Super	hat the intender	nformation
Drilled cement plug and bailed hole Then applied 600# water pressure to ively shut off and pipe cemented in  Subscribed and sworn to before me  24th day of September ,1  Notary Publication of September ,1	to bot casing good	I hereby s given above in Representing	wear or s true and SKELL	affirm the correction Super:	hat the intender	nformation
Drilled cement plug and bailed hole Then applied 600# water pressure to ively shut off and pipe cemented in  Subscribed and sworn to before me  24th day of September ,1  Notary Publications and plug and bailed hole in the subscribed in the subscr	to bot casing good	I hereby s given above in Representing	wear or s true and SKELL	affirm the correct of Super:	hat the intender	nformation