

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	210	210	Caliche, sand & shells
210	325	115	Red Bed, shells & sand(15 3/8" OD csg. - 317')
325	485	160	Red Bed & Shells
485	525	40	Red Rock
525	555	30	Red Bed & Red Rock
555	745	190	Red Bed & Shells Red Bed & Shells
745	780	35	Red Bed & Shells Rustler Lime & Water Sand
780	795	15	Red Bed, Gyp and Anhydrite
795	805	200	Anhydrite and hard sand
805	1076	81	Hard Sand Shells & Red Bed
1076	1170	94	Red Bed, Streaks Hard Sand & Sandy Shale
1170	1490	320	Red Bed & Sandy Shells
1490	1565	75	Anhydrite (9 5/8" OD casing at 1521' 5")
1565	1590	25	Anhydrite & Lime Shells
1590	1625	35	Anhydrite
1625	1929	304	Anhydrite & Salt
1929	1970	41	Anhydrite & Potash
1970	1995	25	Salt & Anhydrite
1995	2259	264	Anhydrite, Salt & Potash
2259	2285	26	Anhydrite & Gyp
2285	2360	75	Salt & Anhydrite
2360	2470	110	Anhydrite, Salt & Potash
2470	2487	17	Anhydrite & Salt
2487	2520	33	Anhydrite
2520	2560	40	Anhydrite & Salt
2560	2720	160	Salt & Potash
2720	2840	120	Broken Anhydrite, Salt & Potash
2840	2880	40	Anhydrite
2880	2920	40	Broken Anhydrite & Salt
2920	2955	35	Anhydrite
2955	3156	201	Anhydrite, Salt & Potash
3156	3183	27	Anhydrite
3183	3365	182	Anhydrite & Salt
3365	3372	7	Anhydrite & Lime
3372	3400	28	Anhydrite
3400	3589	189	Lime (7" OD casing set at 3507')
3589	3601	12	White Lime & Brown Shale
3601	3609	8	Lime
3609	3624	15	Lime & Sandy Shale
3624	3653	29	Lime
3653	3658	5	Saturated Sand
3658	3669	11	Fine Saturated Sand

TOTAL DEPTH ~ 3669'