


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD HOBBS OFFICE
DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Repollo Oil Company Hobbs, New Mexico
Company or Operator Address
C. W. Whitten "B" Well No. 4 in 1/2 of Sec. 4 T. 24S
Lease
R. 363 N. M. P. M. Cooper Field, Lea County.
Well 2310 feet south of the North line and 330 feet west of the East line of 1/2 Sec. 4
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is C. W. Whitten Address.
If Government land the permittee is Address.
The Lessee is Address.
Drilling commenced April 21 1938 Drilling was completed May 13 1938
Name of drilling contractor Sawyer Drilling Co. Address Tulsa, Okla.
Elevation above sea level at top of casing 3415 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3602 to 3650 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
13"	40	8		262	none				
9 5/8"	40	8		1435	float				
7"	24	10		3568	do				
2"	4.6	leg. 3	leg.	3633					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2"	13"	280	250	Kalliburton		
11 1/2"	9 5/8"	1453	400	do		
8 1/2"	7"	3581	250	do		
2"	2" leg.	3639	Tubing			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	none					

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 5/14/38 19
The production of the first 24 hours was 60 barrels of fluid of which 100 % was oil; %
emulsion; % water; and % sediment. Gravity. Be.
If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Ed Tillman Driller Bill Arnold Driller
H. E. Lantz Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

18th

Hobbs, New Mexico

May 18, 1938

Name of Surveyor

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	500		500 Sandstone & bed beds
500	920		420 bed bed, bedrock & lime
920	1360		440 Broken lime & shells
1360	1530		170 Anhydrite
1530	2670		1140 Salt
2670	3120		450 anhydrite & salt
3120	3650		530 Lime