



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

JUN 15 1960 AM 8 13

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

CHAMBERS & KENNEDY

(Company or Operator)

WHITTEN

(Lease)

Well No. 1, in SE $\frac{1}{4}$ of SW $\frac{1}{4}$, of Sec. 9, T. 24 S, R. 36 E, NMPM.

WILDCAT

Pool,

LEA

County.

Well is 660 feet from SOUTH line and 1980 feet from WEST lineof Section 9. If State Land the Oil and Gas Lease No. isDrilling Commenced APRIL 15, 1960 Drilling was Completed JUNE 2, 1960Name of Drilling Contractor HILLIN DRILLING COMPANYAddress WILCO BUILDING, P. O. BOX 1747, MIDLAND, TEXASElevation above sea level at Top of Tubing Head 3379 G. L. The information given is to be kept confidential until NOW, 1960

OIL SANDS OR ZONES

No. 1, from NONE to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 3950 to 5300 feet. 300' of surface (flowed when aerated 300 MPH)No. 2, from 6457 to 6533 feet. 5500' SW on DSTNo. 3, from 6690 to 6780 feet. 1400' SW on DST

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	54	NEW	304	Tex. Pattern	NONE	NONE	SURFACE PIPE
8 5/8	28 & 32	NEW	3936	" "	1020	NONE	SALT STRINGS
7	23	USED	5090	FLOAT SHOE	3916	NONE	INTERMEDIATE

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17	13 3/8	304	100	PUMP & PLUG		
12 1/4	8 5/8	3936	125	" "		
7 7/8	5090	5090	50	" "		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 7337 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19.

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. 1560	T. Devonian	T. Ojo Alamo	
T. Salt. 1580	T. Silurian	T. Kirtland-Fruitland	
B. Salt. 3350	T. Montoya	T. Farmington	
T. Yates. 3489	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers. 3750	T. McKee	T. Menefee	
T. Queen -	T. Ellenburger	T. Point Lookout	
T. Grayburg -	T. Gr. Wash.	T. Mancos	
T. San Andres 5405	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Permian	T.	T. Penn.	
T. Pueblo	T.	T.	
T. Abo. EQUIVALENT 6340	T.	T.	
T. Perm. BONE SPRINGS 7260	T.	T.	
T. Miss.	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	960	960	Surface Rocks				
			Triassic Sands				
960	1560	600	Permian Red Beds				
1560	3380	1820	Anhy, Red Beds, Salt				
3380	3488	108	Tansill Dolo.				
3488	3720	232	Yates Sand				
3720	5405	1625	Seven Rivers } Reef				
			Queen } Dolo.				
5405	6340	935	Delaware Sand				
6340	6540	200	Dolo : Delaware Sand,				
			lower Delaware				
6570	7260	690	Abo Equivalent Reef				
			dolomite				
7260	7337	77	Bone Springs LS &				
			Chert				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

JUNE 8, 1960

(Date)

Company or Operator CHAMBERS & KENNEDY

Address 607 MIDLAND NAT'L BANK BLDG.

Name