

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELL

RECEIVED
JUN 20 1941
HOBBES

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Midland, Texas
Place

June 19, 1941
Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Hobbs

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Co's. Ennis G. Mosley Well No. 1 in the
Company or Operator Lease
SE 1/4 of Sec. 10 T. 24-S, R. 36-E, N. M. P. M.,
Hunice Field, Lea County

The dates of this work were as follows: May 28 to June 11, 1941 Incl.

Notice of intention to do the work was (was not) submitted on Form C-102 on May 7, 1941 19
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cement retainer was set in 5-1/2" casing at 3532', open hole was squeeze cemented. Casing was gun perforated from 3439' to 3525' and perforations acid treated. This section then tested 10 Bbbls. of oil, 600 Bbbls. water, by gas lift. Retainer was set at 3436' and perforations were cemented off. Casing was gun perforated from 3357' to 3404', and perforations were acid treated with the section testing dry both Before and after treatment. There are no higher zones that justify the expense of additional exploration. Since the above attempts have failed to produce any satisfactory results, we are therefore planning an abandonment of this well. Necessary requests will be forwarded. Work supervised by H. S. Mc Garry, Sup't., Humble Oil & Refg. Co., Hobbs, N.M.

Witnessed by No witness necessary. Name Company Title

Subscribed and sworn to before me this 19th

day of June, 1941

T M. ROPER

Midland County, Texas

My Commission expires

I hereby swear or affirm that the information given above is true and correct.

Name R. J. Yarkrough

Position Asst. Division Superintendent

Representing Humble Oil & Refg. Co.,
Company or Operator

Address Box 1600, Midland, Texas

Remarks:

Rog Yarkrough
Name
OIL & GAS INSPECTOR
Title

