
NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained See additional instructions in the Rules and Regulations of the Commission

he Commission. Indicate natu	are of notice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		
Midland, Texas	October 7, 1947 Place Dat	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain w		A
	E. C. Mosley Well No. 2 in	SE/L
of Sec. 10 , T. 21-S , R. 36-	N. M. P. M., Cooper-Jal	Field.
Coun	nt <b>y</b> .	
place cement plug of 50 sacks on the control of 50 sacks are cement plug of 50 sacks at 800	RULES AND REGULATIONS OF THE COMMISSION bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be pl	and tervals
place cement plug of 50 sacks on tall. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1	bettom (T.D. 36hl'). To shoot 52 casing at 2600'. To shoot 7-5/8" casing at 800' and to plug top of hole with cement. In	and tervals
place cement plug of 50 sacks on tall. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1	bettom (T.D. 36hl'). To shoot 52 casing at 2600'. To shoot 7-5/8" casing at 800' and to plug top of hole with cement. In	and tervals
place cement plug of 50 sacks on ball. Place cement plug of 50 sacks at 600 stween plugs to be filled with mad location.	bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be pl	and tervals
place cement plug of 50 sacks on bill. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1 scation.	bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be pl	and tervals
place cement plug of 50 sacks on bill. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1 scation.	bettom (T.D. 36hl'). To shoot 52 casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be plug top of the state of the	and tervals
place cement plug of 50 sacks on bull. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1 cation.	bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be plug top of the strain of the shoot of th	and itervals aced at
place cement plug of 50 sacks on bill. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad 1 scation.	bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be plug top of the state of the	and itervals aced at
place cement plug of 50 sacks on ball. Place cement plug of 50 sacks at 800 tween plugs to be filled with mad location.  Approved	bettom (T.D. 36hl'). To shoot 5½ casing at 2600'. To shoot 7-5/8 casing at 800' and to plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement. In laden fluid. Regulation marker will be plug top of hole with cement.	and itervals aced at