


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



DUPLICATE

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

Midland, Texas

October 23, 1946

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Humble Oil & Refining Company E. C. Mosley Well No. 3 in the  
Company or Operator Lease

SE/4 of Sec. 10, T. 24-S, R. 36-E, N. M. P. M.,  
Cooper-Jal Field, Lea County.

The dates of this work were as follows: October 14 to October 23, 1946

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on October 7, 1946  
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Circulated hole with 10 sacks mud. Placed cement plug of 50 sacks from total depth of 3512' to 3210'. Shot 5 1/2" casing at 2550', 2450' and 2246'. Casing released at 2246'. Recovered 2246.75' of 5 1/2" casing. Placed cement plug of 50 sacks from 2360' to 2110'. Shot 7 5/8" casing at 650', 540' and 450'. Recovered 540' of 7 5/8" casing. Set cement plug of 20 sacks from 475' to 423' and cemented top of hole with 10 sacks. Intervals between plugs filled with mud-laden fluid. Moved off rig, levelled location and installed 4" marker.

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_\_

23rd day of October, 1946

Willie Mae Ferguson  
Notary Public

My commission expires 6-1-47

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position Division Superintendent

Representing Humble Oil & Refining Company  
Company or Operator

Address Box 1600 - Midland, Texas

Remarks:

APPROVED  
Date OCT 28 1946

[Signature]  
Name \_\_\_\_\_  
Oil & Gas Inspector  
Title \_\_\_\_\_