

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Kan-Mex Corporation **Dallas Nat'l. Bank Bldg., Dallas, Texas**
Company or Operator Address
Mosley Well No. **2** in **SW 1/4 SE 1/4** of Sec. **10**, T. **24S**
Lease
R. **36E**, N. M. P. M., **Cooper-Jal** Field, **Lea** County.
Well is **1980** feet south of the North line and **1980** feet west of the East line of **SE 1/4 Sec 10-24S-36E**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is **Ennis C. Mosley** Address **Cisco, Texas**
If Government land the permittee is Address
The Lessee is **Kan-Mex Corporation** Address **Dallas, Texas**
Drilling commenced **July 25,** 19**50** Drilling was completed **August 5,** 19**50**
Name of drilling contractor **R. & R. Drilling Company** Address **Abilene, Texas**
Elevation above sea level at top of casing **3384** feet. **3392'** Derrick Floor
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **3590** to **3620** No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **80** to **160** feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
9-5/8"	36#	8	H-40	1400'	Larkin				
7"	20#	8	J-55	3665'	Larkin		3590	3620	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	9-5/8"	1400'	500	Halliburton		
8-3/4"	7"	3665	200	Halliburton		
2 1/2" tubing		3620				

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
			3000 gals.	8-5-50	3590-3620	

Results of shooting or chemical treatment **Well flowed 55 bbls. oil per day plus 700**
bbls. water

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3665** feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **August 5,** 19**50**
The production of the first 24 hours was **755** barrels of fluid of which **7.3** % was oil; %
emulsion; **92.7** % water; and % sediment. Gravity, Be. **28**
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

R. D. Dewey Driller **H. Gibson** Driller
J. A. McAnally Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **18th**
day of **August**, 19**50**

Vern J. Bartlett
Vern J. Bartlett, Notary Public
Midland County, Texas
My Commission expires **6-1-51**

Midland, Texas **8-18-50**
Name *P. H. Sch. 10*
Position **Agent**

Representing **Kan-Mex Corporation**
Company or Operator
Address **1203 Dallas National Bank Bldg.**
Dallas, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	60	60	Caliche
60	250	190	Sand and red bed
250	300	50	Red rock
300	480	180	Red shale
480	725	245	Red shale and red rock
725	900	175	Red rock
900	1015	115	Red shale
1015	1240	225	Red rock
1240	1300	60	Red sand
1300	1395	95	Anhydrite
1395	1580	185	Salt and anhydrite
1580	1650	70	Anhydrite and red rock
1650	1900	250	Anhydrite and salt
1900	2250	350	Salt and potash
2250	2590	340	Salt
2590	2880	290	Anhydrite and salt and potash
2880	3040	160	Salt and potash
3040	3130	90	Salt
3130	3160	30	Anhydrite
3160	3300	140	Brown Lime
3300	3440	140	Lime and sand - odor oil
3440	3560	120	Lime and sand - odor oil
3560	3590	30	Soft lime - good odor oil
3590	3620	30	Soft lime - good odor oil
3620	3665	45	Soft lime - slight odor oil