

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator JOSEPH I. O'NEILL, JR.	8. Farm or Lease Name ROCKET
3. Address of Operator P. O. BOX 2840, MIDLAND, TEXAS 79702	9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 10 TOWNSHIP 24S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat JALMAT
15. Elevation (Show whether DF, RT, GR, etc.) 3381' GR	12. County LEA

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PBTD 3577'. Well was completed in the Yates formation through perforations at the following depths: 3432-3440', 3468-3482', 3506-3514' and 3534-3546'.  
5½" casing set at 3623' w/top of cement at 2768'.  
8-5/8" casing set at 308' w/cement circulated to surface.

As well is non-commercial, we propose the following:

- (1) Set Plug #1, 40 sacks regular cement from 3230 to 3430'.
- (2) Fill hole w/mud laden fluid.
- (3) 100' plug at 5½" casing stub at approx 2700'.
- (4) Set Plug #2, 50 sacks regular cement from 1400 to 1500'.
- (5) Set Plug #3, 50 sacks regular cement from 250 to 350'.
- (6) Set Plug #4, 10 sacks regular cement from 3 to 20'.
- (7) Weld on cap and State marker.

If 5½" casing is stuck in the red bed, will cut off at free point.

THIS INFORMATION MUST BE RECEIVED 24 HOURS PRIOR TO THE BEGINNING OF DRILLING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert Bigard TITLE FIELD FOREMAN DATE 1-29-79  
APPROVED BY Jerry Sexton DATE JAN 31 1979  
CONDITIONS OF APPROVAL, IF ANY: