

NEW MEXICO STATE LAND OFFICE  
OFFICE OF THE STATE GEOLOGIST  
SANTA FE, NEW MEXICO

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas inspector if possible.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON RESULT OF SHOOTING WELL REPORT ON RESULT OF TEST OF WATER SHUT-OFF REPORT ON RESULT OF ABANDONMENT OF WELL	REPORT ON DEEPENING WELL REPORT ON PULLING OR OTHERWISE ALTERING CASING REPORT ON REPAIRING WELL <b>Report On Perforating Casing</b>
---	---

**Hobbs, New Mexico 11/29/35**

Place

Date

Mr. **E.H. Wells** State Geologist,  
Santa Fe, N. Mex.

Following is a report on the work done and the results obtained under the heading noted above at the **Simms Oil Company J.L. Coates** Well No. **1** in the  
Company or Operator **NEC** of Sec **10**, T **24**, R **36** N. M. P. M.,  
**Cooper** Oil Field, **Lea** County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was ~~submitted~~ submitted on Form SG **102** on **11/20/35** 19\_\_\_\_, and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was drilled to 3700' and tested all sulphur water. Plugged back to 3566' and treated with 2000-gallons acid and showed a very small amount of water, shot with 160-quarts glycerene and tested 3-bbls. per hour of 100% sulphur water. Plugged back to bottom of casing (3565') with cement then perforated casing from 3547' to 3563' with 30-holes by the Lane-Wells Company. Bailed well down to 2200' but could not lower below 2200', all sulphur water with very small show gas.

Subscribed and sworn to before me this

\_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_

Notary Public

My Commission expires \_\_\_\_\_

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name **F. Schindler - Lgt.**

Position **Prod. Sup't**

Representing **Simms Oil Company**  
Company or Operator

Address **Drawer "KK" Hobbs N.M.**

Name

Title

OFFICE OF THE STATE GEOLOGIST  
STATE OF ALABAMA  
BIRMINGHAM, ALA.

REGULATIONS FOR THE PROTECTION OF MINES

It is the policy of the State of Alabama to protect the life and property of its citizens by enforcing the laws relating to the safety of mines. It is the duty of the State Geologist to enforce these laws and to see that the mines are safe for the workers. The following regulations are hereby adopted for the protection of mines:

Section 1. The following regulations shall be enforced by the State Geologist:

1. Every mine shall be inspected by the State Geologist at least once a year.
2. Every mine shall be kept in a safe condition at all times.
3. Every mine shall be kept free from fire and other dangers.
4. Every mine shall be kept free from gas and other dangerous substances.
5. Every mine shall be kept free from water and other dangerous substances.
6. Every mine shall be kept free from rocks and other dangerous substances.
7. Every mine shall be kept free from other dangerous substances.
8. Every mine shall be kept free from other dangerous substances.
9. Every mine shall be kept free from other dangerous substances.
10. Every mine shall be kept free from other dangerous substances.

It is the policy of the State of Alabama to protect the life and property of its citizens by enforcing the laws relating to the safety of mines. It is the duty of the State Geologist to enforce these laws and to see that the mines are safe for the workers. The following regulations are hereby adopted for the protection of mines:

Section 1. The following regulations shall be enforced by the State Geologist:

1. Every mine shall be inspected by the State Geologist at least once a year.
2. Every mine shall be kept in a safe condition at all times.
3. Every mine shall be kept free from fire and other dangers.
4. Every mine shall be kept free from gas and other dangerous substances.
5. Every mine shall be kept free from water and other dangerous substances.
6. Every mine shall be kept free from rocks and other dangerous substances.
7. Every mine shall be kept free from other dangerous substances.
8. Every mine shall be kept free from other dangerous substances.
9. Every mine shall be kept free from other dangerous substances.
10. Every mine shall be kept free from other dangerous substances.

It is the policy of the State of Alabama to protect the life and property of its citizens by enforcing the laws relating to the safety of mines. It is the duty of the State Geologist to enforce these laws and to see that the mines are safe for the workers. The following regulations are hereby adopted for the protection of mines:

Section 1. The following regulations shall be enforced by the State Geologist:

1. Every mine shall be inspected by the State Geologist at least once a year.
2. Every mine shall be kept in a safe condition at all times.
3. Every mine shall be kept free from fire and other dangers.
4. Every mine shall be kept free from gas and other dangerous substances.
5. Every mine shall be kept free from water and other dangerous substances.
6. Every mine shall be kept free from rocks and other dangerous substances.
7. Every mine shall be kept free from other dangerous substances.
8. Every mine shall be kept free from other dangerous substances.
9. Every mine shall be kept free from other dangerous substances.
10. Every mine shall be kept free from other dangerous substances.