


DUPLICATE**OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS

REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL

REPORT ON RESULT OF TEST OF CASING SHUT-OFF

REPORT ON RESULT OF PLUGGING OF WELL

REPORT ON REPAIRING WELL

REPORT ON PULLING OR OTHERWISE ALTERING CASING

REPORT ON DEEPENING WELL

December 10, 1946

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation **G. E. Cooper** Well No. **2** in the
Company or Operator Lease

NW SW of Sec. **11**, T. **24-S**, R. **36-E**, N. M. P. M.,
Cooper Field, **Lee** County.

The dates of this work were as follows: **November 1, 1946, to November 9, 1946**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **March 4,** 1946
and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set Baker cement retainer at 3482', squeezed with 15 sacks cement. Mudded hole with 60 sacks Baroco, shot 5-1/2" casing off at 3060', recovered 3053' of 5-1/2" casing. Left 452' of 5-1/2" casing in hole. Set a 15 sack cement plug on top of 5-1/2" casing at 3060'. Shot 7-5/8" casing off at 2610', recovered 2587' of same. Left 447' of 7-5/8" casing in hole. Set a 10 sack cement plug at 1300', mudded hole to near the surface, left 297' of 10-3/4" in hole, and set 15 sack plug at surface with 4' x 4" marker set in accordance with State regulations.

Witnessed by **Glenn Staeh** **Gulf Oil Corporation** **Foreman**
Name Company Title

Subscribed and sworn before me this

10th day of **December**, 19**46**

W. H. Vaughan
Notary Public

My commission expires **Oct. 24, 1949**

I hereby swear or affirm that the information given above is true and correct.

Name **E. J. Gallagher**

Position **District Superintendent**

Representing **Gulf Oil Corporation**
Company or Operator

Address **Box 1667, Hobbs, New Mexico**

Remarks: **APPROVED**Date **DEC 11 1946**

Roy Yarbrough
Oil & Gas Inspector
Title