

Submit 3 Copies To Appropriate District  
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-09542

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

140600

7. Lease Name or Unit Agreement Name:

Cooper G

8. Well No.

1

9. Pool name or Wildcat

Jalmat (Tansill Yates 7 Rivers)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

David H. Arrington Oil & Gas, Inc

3. Address of Operator

P.O. Box 2071, Midland, TX 79702

4. Well Location

Unit Letter K : 1320 feet from the South line and 1320 feet from the West line

Section 11

Township 24S

Range 36E

NMPM Lea

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- 2990'
1. Set CIBP at ~~3990'~~ and cap with 35' of cement. Tag cement.
  2. Spot 25 sxs plug or 100' plug (which ever is greater at 1300').
  3. Spot 100' cement plug across 9 5/8" surface casing shoe at 310'. -TAG
  4. Spot 10 sxs cement plug at surface and set dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24  
HOURS PRIOR TO THE BEGINNING OF  
PLUGGING OPERATIONS FOR THE C-103  
TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chuck Sledge TITLE Engineer DATE 8/20/01

Type or print name Chuck Sledge

Telephone No. (915) 682-6685

(This space for State use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of approval, if any:

FILED

5  
C



**(2 STRING CSNG)**

LEASENAME COOPER "G"

SECT 11 TWN

FROM 1320 SL

**TD:**

**PBTD:**

WELL #

248 RNC

1320 1320 W L

**FORMATION @ TD**

FORMATION @ PBTD

9 5/8  
@ 310  
TOC

7"  
@2997  
TOC

shot hole

TD 3207

	SIZE	SET @	TOC	TOC DETERMINED BY	
SURFACE					
INTMED 1					
INTMED 2					
PROD					
	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					
	CUT & PULL @			TOP - BOTTOM	
INTMED 1			PERFS	-	
INTMED 2			OPENHOLE	-	
PROD					

**\*REQUIRED PLUGS DISTRICT I**

RUSTLER (ANHYD)	
YATES	3150
QUEEN	
GRAYBURG	
SAN ANDRES	
CAPTIAN REEF	
DELAWARE	
BELL CANYON	
CHERRY CANYON	
BRUSHY CANYON	
BONE SPRING	
GLORIETA	
BLINEBRY	
TUBB	
DRINKARD	
ABO	
WC	
PENN	
STRAWN	
ATOKA	
MORROW	
MISS	
DEVONIAN	

[illegible]

