


NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico



MISCELLANEOUS NOTICES

HOBBS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

legulations of		Indica	te nature	of no	tice by checking	below:			
NOTICE OF SHUT-O	INTENTION FF	TO TEST CA	ASING	×		'INTENTION CALLY TREAT		OR	
NOTICE OF	INTENTION	TO CHANGE	E PLANS			INTENTION WISE ALTER		OR	
NOTICE OF	INTENTION	TO REPAIR	WELL						
NOTICE OF	INTENTION	TO DEEPEN	WELL		NOTICE OF	INTENTION	TO PLUG	WELL	
				H	obbs, New 1	lexi.co	June	19,	1941
IL CONSER anta Fe, Ne entlemen:	RVATION COL	MMISSION,			Place			Date	
	notice of inte	ntion to do c	ertain wor	k as d	escribed below a	t the			
-					Cooper				
Company	or Operator		Lease						
		-			N. M. P. M.,	Coc	per	·	Fie
1.6	<u>a</u>		.County.						
od o	rilled to ottom wit ellar - E	1209' s th 300 s fallibur	and ran k cemen	n and	AND REGULAT d cemented circulated s used. Wi	9-5/8" OI l back to	oasin bottom	g on of ours	•
)d)0 (a	rilled to ottom wit ellar - F nd on Fri	1209' s th 300 so Halliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated	9-5/8" OI l back to ill let se eximately	oasin bottom	g on of ours	
)d)0 18	rilled to ottom wit ellar - F nd on Fri	1209' s th 300 so Halliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to ill let se eximately	oasin bottom	g on of ours	•
)d)0 (8	rilled to ottom wit ellar - F nd on Fri	1209' s th 300 so Halliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to ill let se eximately	oasin bottom	g on of ours	•
)d)0 (8	rilled to ottom wit ellar - F nd on Fri	1209' s th 300 so Halliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to ill let se eximately	oasin bottom	g on of ours	•
)d)0 (8	rilled to ottom wit ellar - F nd on Fri ill drill	1209's in 300 so salliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to ill let se eximately	oasin bottom	g on of ours	•
be ea w	rilled to ottom wit ellar - F nd on Fri ill drill	1209' s th 300 so Halliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to lll let se eximately nut-off.	oasin bottom	g on ours,	•
pproved	rilled to ottom witelar - Find on Friill drill	1209's in 300 so salliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated s used. Wi l, at appro	9-5/8" OI l back to lll let se eximately nut-off.	casin bottom t 72 h	g on ours,	•
pproved	rilled to ottom witelar - Find on Friill drill	1209's in 300 so salliburi	and rank comer ton Pro	n and nt + 000s 194	d cemented circulated sused. Wi l, at appror casing sl	9-5/8" OI hack to the lil let se the limstely nut-off. SKELLY OIL Company of the little litt	casing bottom t 72 h 11:00	g on of ours. A. M	ent
pproved	rilled to ottom witelar - Find on Friill drill	209's 1209's 14300 s 1411'bur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur	and rank cemer ton Prone 20, and test	n and nt + 000s 194	d cemented circulated s used. Wi l, at appropriate casing sl	9-5/8" OI l back to lll let se eximately nut-off.	casin bottom t 72 h 11:00	g on of lours, A. M	ent
pproved	rilled to ottom witelar - Find on Friill drill	209's 1209's 14300 s 1411'bur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur	and rank cemer ton Prone 20, and test	n and nt + 000s 194	d cemented circulated sused. Wi l, at appror casing sl By Position Send Name	9-5/8" OI let se cuima tely nut-off. SKELIY OII Company of the communications	casing bottom to t 72 h 11:00	g on of lours. A. M	ent
be ea w:	rilled to ottom with ellar - Fond on Friill drill	209's 1209's 14300 s 1411'bur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur 14ay, Jur	and rank cemer ton Prone 20, and test	n and nt + 000s 194	d cemented circulated sused. Wi l, at appror casing sl By Position Send Name	9-5/8" OI back to the literate of the literate	casing bottom to t 72 h 11:00	g on of lours. A. M	ent

The Control of the said of the 4.4**46 (発行** しょうこう (第二) カライギ

THE SECTION COSTS WAS ASSESSED.

The control of the co

in the second of the second o

DEFECT CONTRACTOR STATES SET OF THE STATES O

The final points of the θ -constant θ -. 🖟 🕟 Presidentification of the Company of the Co and the second s

Appleading State of the second nyma na jijan yasa

A Commence of the Second Second

March Carlotte & March

Additional Section (1997) and the second section of the second section (1997).