

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## Notice of Intention to Drill

JUN 12 1941

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

June 11, 1941

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.  
Gentlemen:

Place

Date

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

- J. W. Cooper

Well No. 1 in ONE SW

of Sec. 12, T. 24, R. 36, N. M. P. M., Lease Cooper, Field, Lea County

N.

The well is 1980 feet (N.) ~~xxx~~ of the ~~1200 S.~~ line and 1980 feet (E.) (~~xxx~~ of the West line of Section 12 -

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_, Assignment No. \_\_\_\_\_

If patented land the owner is Jos. W. Cooper


Address Jal, New Mexico

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Skelly Oil Co.

Address Tulsa, Oklahoma



AREA 640 ACRES  
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary tools top to total depth. Contractor - Lee Drilling Co. - Tulsa, Okla.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
11 1/2"	9-5/8" OD	36 Lbs.	New	1150'	Cemented	300
8 1/2"	7"	20 Lbs.	New	3350'	Cemented	250

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about \_\_\_\_\_ feet.

Additional information: In cementing the 9-5/8" OD casing the cement will be circulated back to bottom of cellar. The cement shall be allowed sufficient time to thoroughly set before plug is drilled. Halliburton will be used in cementing both strings.

Approved \_\_\_\_\_, 19 \_\_\_\_\_

except as follows: \_\_\_\_\_

Sincerely yours,

SKELLY OIL COMPANY

Company or Operator

By \_\_\_\_\_

Position District Superintendent

Send communication regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico..

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

OIL & GAS INSPECTOR

Title \_\_\_\_\_

Time of subject to subject

100

100

the 1990s, the number of people in the United States who are 65 years of age or older is projected to increase from 20 million to 30 million, and the number of people 75 years of age or older is projected to increase from 10 million to 15 million (U.S. Census Bureau, 1997).

100

1.  $\frac{1}{2} \times \frac{1}{2} = \frac{1}{4}$

Figure 1. The effect of the concentration of the inhibitor on the rate of polymerization of  $\alpha$ -methylstyrene in the presence of  $\text{SnCl}_4$  at  $25^\circ\text{C}$ .

— *Journal of the American Medical Association*, 1997

[illegible]

THE UNIVERSITY OF CHICAGO LIBRARY

[illegible]

1. *Phragmites australis* (Cav.) Trin. ex Steud.

1. *Chlorophyll a* and *Chlorophyll b* were determined by the method of Arar and Collins (1971) using a Shimadzu 1010 spectrophotometer.

U. Hoffmann, J. K. Kuehn, and M. J. Griffin

[illegible]