

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

| | |
|---|---|
| WELL API NO. 30 025 09562 | |
| 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> | |
| 6. State Oil / Gas Lease No. | |
| 7. Lease Name or Unit Agreement Name COOPER JAL UNIT | |
| 8. Well No. 304 | 9. Pool Name or Wildcat Jalmat (Yates) Gas |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMI (FORM C-101) FOR SUCH PROPOSALS.

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator
PO BOX 3109, MIDLAND, TX 79702

4. Well Location
Unit Letter J : 1650 Feet From The SOUTH Line and 1650 Feet From The EAST Line
Section 13 Township 24S Range 36E NMPM LEA COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3325

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

| | | | |
|--|---|--|--|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPERATION <input type="checkbox"/> | PLUG AND ABANDONMENT <input checked="" type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |
| OTHER: <input type="checkbox"/> | | OTHER: <input type="checkbox"/> | |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-26-95

Tag cement @ 1250. Pull up to 943' & load hole w/mud.
Set 5 1/2 pkr @ 442'. Establish rate of 2BPM @ 200#. Full returns up annulus, none above pkr.
Set 5 1/2" cement retainer on tbg at 442'.
Squeeze 160 sx cement below retainer to surface up 5 1/2" annulus.
Circulate 40 sx cement to surface inside 5 1/2".
Cut off Bradenhead and install dry hole marker (4-26-95)
NMOC notified by Pool.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John Ayers TITLE Administrative Supvr DATE 10/16/01
TYPE OR PRINT NAME John Ayers Telephone No. 915-688-4580

(This space for State Use)

APPROVED [Signature] TITLE Ad Rep DATE 1-28-02
CONDITIONS OF APPROVAL IF ANY ☐

3
C
5

9