sizes, weights, and lengths of prop all other important proposed work

Set cement plug from 3710 - 3310 w/70 sx 50-50 Pozmix Incor 4% gel 2% Cal. CL2, 3/4% 2792 - 2292 w/116 sx " CFR-2-" 1800 - 1000 w/236 sx " 355 - 250 w/23 sx " 28 - 0 w/15 sx

Geophones set at 3700, 3650, 3600, 3550, 3500, 3450, 2600, 2550, 2500, 1300, 1250, and 1200'.

Installed dry hole marker as required by NMCC. U.S.G.S.

Location cleaned and leveled.

1	understand that this plan	of work must receive approva	l in writing by the Geolog	gical Survey before ope	stations may be commenced

0		Title Agent		
	Hobbs, New Mexico	ByORIGINAL A. L CARPENTER		
Address	Box 2347	ORIGINAL A 1 CADDENTER	<u> </u>	
Company	HUMBLE OIL & REFINING COMPANY	,		

APPEVED COP	Budget Bureau No. 42-R358.6 Approval expires 12-31-60.
(2 00. 1002)	T IN TRIPLICATE) Land Office Santa Fe
UNIT	TED STATES Long No. 1 NM-040763
FIRICT ENGINEERAR MEN	NT OF THE INTERIOR OGICAL SURVEY
	SOURCE SOURCE
SUNDRY NOTICES A	AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALICE CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ARGYE BY CHECK MARI	K NATURE OF REPORT, NOTICE, OR OTHER BATA)
	April 26
No. 1 Federal	April. 26
The elevation of the derrick floor above sea le	or Subdivision) (State or Territory)
•	ILS OF WORK
(State names of and expected depths to objective sands; show si	izes, weights, and lengths of proposed casings; indicate mudding jobs, cemer other important proposed work)
cmt plug from 2800-2300 w/116 sx 50-50	Pozmix Incor 4% gel 2% Cal. CL2, 3/4% CFR-2 Pozmix Incor 4% gel 2% Cal. CL2, 3/4% CFR-
" " 350 -250 w/23 sx " " 25 -0 w/ 2/10 sx	
	550, 3500, 3450, 2600, 2550, 2500, 1300, 1
phones to be set at 3700, 3650, 3600, 3	550, 3500, 3450, 2600, 2550, 2500, 1300, 1
phones to be set at 3700, 3650, 3600, 3	550, 3500, 3450, 2600, 2550, 2500, 1300, 1
phones to be set at 3700, 3650, 3600, 3	550, 3500, 3450, 2600, 2550, 2500, 1300, 1
phones to be set at 3700, 3650, 3600, 3 1200'.	n writing by the Geological Survey before operations may be commenced.
phones to be set at 3700, 3650, 3600, 3 1200'.	n writing by the Geological Survey before operations may be commenced.
phones to be set at 3700, 3650, 3600, 3 1200'.	PANY

Agent

Title ...