CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office	
DISTRICT I OIL CONSERVATIO	I WELL APLNO
P.O. Box 1980, Hobbs NM 88240 P.O. Box 20	7カ・カンケーカタドタダ
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico	5. Indicate Type of Lease
DISTRICT III	STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WEL	V/////////////////////////////////////
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PEI	OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.)	WOOLWORTH, C. D.
1. Type of Well: OIL GAS WELL X WELL OTHER	
2. Name of Operator	8. Well No.
Phillips Petroleum Company	008
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	9. Pool name or Wildcat JALMAT-YATES
4. Well Location	UNLINI-INILS
Unit Letter 0: 660 Feet From The SOUTH Line and 1980 Feet From The EAST Line	
Section 22 Township 24-S R	36 E 176774 154
Section 22 Township 24-S R	ange 36-E NMPM LEA County er DF, RKB, RT, GR, etc.)
	3341.9
- -	Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB
OTHER:	OTHER:
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed	
work) SEE RULE 1103.	
1. THIS IS A RULE 118 WELL. 2. MIRU SIERRA WELL SERVICE, NU BOPE, GIH W/WS AND SET 5-1/2" CIBP @ 3150', CIRC CSG	
W/9.5 PPG MUD LADEN FLUID.	
3. ALL CEMENT PLUGS WILL BE CLASS "C", MIXED AT 14.8 PPG.	
4. SPOT PLUG NO. 1, 30 SXS, 3150'-2980', COVERS YATES & TANSILL.	
5. SPOT PLUG NO. 2, 35 SXS, 2100'-1810', COVERS TOC AND OLD SQUEEZE @ 1910'. 6. FREEPOINT & PULL 5-1/2" CASING, NEED TO PULL 1400'.	
7. SPOT PLUG NO. 3, 85 SXS, 1450'-1293', WOC & TAG, COVERS THE 9-5/8" SHOE & SALT TOP.	
8. PERF 9-5/8" CSG @ 260', PUMP PLUG NO. 4, 175 SXS DOWN 9-5/8" CSG THRU PERFS @ 260' AND	
BACK TO SURFACE ON 12-1/2" & 9-5/8" ANNULUS, LEAVING THE 9-5/8" CSG FULL.	
9. CUT OFF CSG, INSTALL MONUMENT MARKER, PERFORM RECLAMATION WORK ON LOCATION.	
I hereby certify that the information above is true and complete to the best of my knowledge	and belief.
SKGNATURE Sanjor Regulation Analyst DATE 04/18/96	
IIILE SEITIOF REGULATION ANALYST DATE U4/18/96	
TYPE OR PRINT NAME arry M. Sanders Telephone No. (915)368-1488	
(This space for State Use)	
ORIGINAL SIGNED BY JERRY SEXTON	APR 2.3 1996
DISTRICT I SUPERVISOR APPROVED BY	E' DATE

10 PER DECEMBER OF CHIEF CIO3

υK **36**